

- High protection rating IP 65 – for use in outdoor applications
- Optimised illumination
- 360° visibility
- Simple connection by means of 6.3 mm spades
- Bulb change via removal of dome
- Suitable for use in the 22 mm standard control panel/switch gear programme



206



207/208

TECHNICAL SPECIFICATIONS:

Housing:	PA fibreglass, high-impact
Dome:	PC, transparent (206) PC, transparent; Ring: PC (207/208)
Connection:	Spades 6.3 x 0.8 mm Finger-proof model according to BGV A2, when used with insulated spades

PERMANENT LIGHT 206

Fixing:	Installation mounting for Ø22.5 mm (M 22) with anti-twist device
Dimensions (Diameter x Height):	57 mm x 53 mm
Operating voltage:	max. 48 V
Bulb socket:	B 15 d 5 Watt max.
Bulb change:	via removal of dome
	Bulb not included in assembly

LED PERMANENT LIGHT 207

Fixing:	Installation mounting for Ø22.5 mm (M 22) with anti-twist device
Dimensions (Diameter x Height):	57 mm x 69 mm
Starting current:	< 0.5 A (at 24 V)
Operating voltage:	24 V ≙, 115 V ~, 230 V ~
Current consumption:	45 mA at 24 V 25 mA at 115 V 25 mA at 230 V

Life duration
up to 100,000 hrs

FLASHING LIGHT 208

Fixing:	Installation mounting for Ø22.5 mm (M 22) with anti-twist device
Dimensions (Diameter x Height):	57 mm x 69 mm
Flash frequency:	c. 0.75 Hz
Flash energy:	1 Ws
Life duration:	4 x 10 ⁶ flashes
Operating voltage:	24 V =, 115 V ~, 230 V ~
Current consumption:	100 mA at 24 V 25 mA at 115 V 30 mA at 230 V

M 22 x 1.5 mm





Bulb change via removal of dome
(LED bulb as accessory)



ORDER SPECIFICATIONS:

Permanent light	12-48 V		
red	206 100 00		
green	206 200 00		
yellow	206 300 00		
clear	206 400 00		
blue	206 500 00		
LED Permanent	24 V ≐	115 V ~	230 V ~
red	207 100 75	207 100 67	207 100 68
green	207 200 75	207 200 67	207 200 68
yellow	207 300 75	207 300 67	207 300 68
clear	207 400 75	207 400 67	207 400 68
blue	207 500 75	207 500 67	207 500 68
Flashing light	24 V =	115 V ~	230 V ~
red	208 100 55	208 100 67	208 100 68
yellow	208 300 55	208 300 67	208 300 68
clear	208 400 55	208 400 67	208 400 68
blue	208 500 55	208 500 67	208 500 68

ACCESSORIES:

Bulb BA 15d	Voltage	
Total length max. 42 mm	12 V, 5 W	955 840 34
	24 V, 5 W	955 840 35
	30 V, 5 W	955 840 32

LED Bulb BA 15d (only for permanent beacon 206)

Total length max. 42 mm	
Voltage	24 V ≐
Current consumpt.	< 45 mA
red	956 100 75
green	956 200 75
yellow	956 300 75
white	956 400 75
blue	956 500 75

TECHNICAL DIAGRAMS

see page 146