



RS stock number : 725-9934



cynergy3 components™

SSH66XU Series

Compact Horizontal Stainless Steel Floatswitch
1/2" NPT Internal or External Fitting



- **Stainless Steel**
- **External/Internal Mount (1/2" NPT)**
- **N/O or N/C switching action**
- **Operating Temp upto 120 °C**
- **Quick Fitting**

The SSH66U series of floatswitches are horizontal floatswitches which offer the choice of internal or external mounting threads.

Thread size is 1/2" NPT.

Manufactured from High Grade 316 stainless steel, they are ideal for food grade applications.

Floatswitch can be fitted to achieve either N/O or N/C configuration by simply rotating through 180 degrees.

All Cynergy3 floatswitches are fitted with high quality reedswitch contacts for optimum performance.


Technical Specification			
Mounting style	External	Cable length - standard	100cm
Mounting thread	1/2" NPT	Cable size	17/0.10 - AWG22
Float/Stem material	316/304 grade	Cable conductor material	Tinned copper
Maximum Temperature	120 °C	Cable sheath material	XLPE
Maximum Pressure	10 bar	Cable temperature rating	125 °C
Float SG	0.7	Sealing gasket	N/A
Minimum Fluid SG	0.75	Tightening torque for fixing	2.0kg/cm

Electrical Specification	
Contact Form	N/O or N/C
Switching Power Max. VA	1
Switching Current Max. A	0.1
Switching Voltage Max AC V	24
Switching Voltage Max DC V	24

All ratings are for resistive load only.

RS Stock No.	Cynergy3 Part	Leadouts
725-9934	SSH66XU12N100	100cm XLPE wires

Mechanical Dimensions (mm)



Cynergy3 Components Ltd.
7 Cobham Road
Ferndown Industrial Estate
Wimborne, Dorset BH21 7PE
Telephone +44 (0) 1202 897969

Email:sales@cynergy3.com

ISO 9001 CERTIFIED

www.cynergy3.com