

Cable - FLKMIL-50/4FLK14/EZ-DR/1000/CS - 2306980

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Assembled round cable with a 50-pos. socket strip and four 14-pos. socket strips, for splitting 32 channels into 4 x 8 channels. The cable is suitable for the ADV561 and ADV161 boards. Cable length: 10.0 m



Key commercial data

Packing unit	1 pc
GTIN	 4 017918 965785
Weight per Piece (excluding packing)	1549.3 g
Custom tariff number	85444290
Country of origin	Germany
Note	Made to Order (non-returnable)

Technical data

General

Nominal voltage U_N	30 V DC
Max. current carrying capacity per path	500 mA (Up to 55°C ambient temperature)
Max. conductor resistance	0.16 Ω /m
Length of cable	10 m
Single wire, cross section	0.14 mm ²
AWG	26
Conductor construction: Number of litz wires:	7
Single wire, material	Cu tin-plated
External diameter	11 mm
Shielding	yes
Outer sheath, material	PVC
External sheath, color	Gray RAL 7035

Environmental conditions

Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C

Cable - FLKMIL-50/4FLK14/EZ-DR/1000/CS - 2306980

Technical data

Environmental conditions

Flame resistance	IEC 60332-1
Resistance to oil	DIN VDE 0472 Part 803, test type B
Gasoline resistance	Against occasional splashes

Connector, module side

Number of positions	14
Connectors	IDC/FLK socket strip (2.54 mm)
Number of plugs	4

Connector, controller side

Number of positions	50
Connectors	IDC/FLK socket strip (2.54 mm)
Number of plugs	1

Supported controller

Controller	YOKOGAWA CENTUM CS3000R3
- suitable I/O card	ADV161
	ADV561
Controller	YOKOGAWA STARDOM
- suitable I/O card	NFDV161
	NFDV561

Classifications

eCl@ss

eCl@ss 4.0	27060306
eCl@ss 4.1	27060306
eCl@ss 5.0	27061801
eCl@ss 5.1	27061801
eCl@ss 6.0	27061801
eCl@ss 7.0	27061801
eCl@ss 8.0	27249205

ETIM

ETIM 2.0	EC000237
ETIM 3.0	EC000237
ETIM 4.0	EC000237
ETIM 5.0	EC000237

UNSPSC

UNSPSC 6.01	26121620
UNSPSC 7.0901	26121620
UNSPSC 11	26121620

Cable - FLKMIL-50/4FLK14/EZ-DR/1000/CS - 2306980

Classifications

UNSPSC

UNSPSC 12.01	26121620
UNSPSC 13.2	26121620

Approvals

Approvals

Approvals

EAC

Ex Approvals

Approvals submitted

Approval details

EAC

Drawings

Cable - FLKMIL-50/4FLK14/EZ-DR/1000/CS - 2306980

Connection diagram

50-pos. connector to the I/O card	4 x 14-pos. connector to the module	Wire color
50	1	black
49	3	brown
48	5	red
47	7	orange
46	9	yellow
45	11	green
44	13	blue
43	15	violet
42	44	gray
41	39	white
40	17	white-black
39	19	white-brown
38	21	white-red
37	23	white-orange
36	25	white-yellow
35	27	white-green
34	29	white-blue
33	31	white-violet
32	43	white-gray
31	37	brown-black
30	2	brown-red
29	4	brown-orange
28	6	brown-yellow
27	8	brown-green
26	10	brown-blue
25	12	brown-violet
24	14	brown-gray
23	16	brown-white
22	42	green-black
21	36	green-brown
20	18	green-red
19	20	green-orange
18	22	green-blue
17	24	green-violet
16	26	green-gray
15	28	green-white
14	30	yellow-black
13	32	yellow-brown
12	41	yellow-red
11	34	yellow-orange