

Inline terminal - IB IL 24 PWR IN/PS-PAC - 2863135

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Inline power terminal, complete with accessories (connection plug and labeling field), 24 V DC, for system voltages U_M , U_S , U_L , U_{ANA}

The illustration shows the version IB IL 24 PWR IN/R-PAC

Product description

The terminal feeds the voltage to an Inline station if there is no bus terminal module, e.g. in the case of ILC 200 UNI. A 24 V DC voltage (U_{24V}) is applied to the terminal. This provides the logics voltage (U_L) and the supply voltage for the analog terminals (U_{ANA}). The terminal also allows the 24 V DC main voltage (U_M) and the 24 V DC segment voltage (U_S) to be supplied.

Why buy this product

- Supplies all 24 V DC voltages required for the low-level signal
- Diagnostic and status indicators



Key commercial data

Packing unit	1 pc
GTIN	 4 017918 917265
Weight per Piece (excluding packing)	132.0 g
Custom tariff number	85389091
Country of origin	Germany
Note	Made to Order (non-returnable)

Technical data

Note

Utilization restriction	EMC: class A product, see manufacturer's declaration in the download area
-------------------------	---

Dimensions

Width	48.8 mm
Height	119.8 mm
Depth	71.5 mm

Interfaces

Inline terminal - IB IL 24 PWR IN/PS-PAC - 2863135

Technical data

Interfaces

Connection method	Inline data jumper
Interface	Inline local bus

Power supply

Communications power U_L	7.5 V DC $\pm 5\%$
I/O voltage range	19.2 V ... 30 V
Max. current consumption	1.25 A DC

General

Weight	132 g
--------	-------

Inline potentials

Communications power U_L	7.5 V DC $\pm 5\%$
Power supply at U_L	2 A DC (observe derating)
Main circuit supply U_M	24 V DC (nominal value)
Supply voltage range U_M	19.2 V ... 30 V (including all tolerances, including ripple)
Power supply at U_M	8 A (nominal value)
Segment supply voltage U_S	24 V DC -15 % / +20 % (acc. to EN 61131-2)
Power supply at U_S	8 A (nominal value)
I/O supply voltage U_{ANA}	24 V DC -15 % / +20 % (acc. to EN 61131-2)
Power supply at U_{ANA}	0.5 A DC (observe derating)

Classifications

eCl@ss

eCl@ss 4.0	27250308
eCl@ss 4.1	27250304
eCl@ss 5.0	27250304
eCl@ss 5.1	27242610
eCl@ss 6.0	27242610
eCl@ss 7.0	27242610
eCl@ss 8.0	27242610

ETIM

ETIM 2.0	EC001433
ETIM 3.0	EC001600
ETIM 4.0	EC001600
ETIM 5.0	EC001600

UNSPSC

UNSPSC 6.01	43172015
UNSPSC 7.0901	43201404

Inline terminal - IB IL 24 PWR IN/PS-PAC - 2863135

Classifications

UNSPSC

UNSPSC 11	43172015
UNSPSC 12.01	43201404
UNSPSC 13.2	43201404