

Main

Range of product	Zelio Logic
Product or component type	Modular smart relay
[Us] rated supply voltage	100...240 V AC
Discrete input number	6
Number of outputs	4 relay

Complementary

Local display	With
Supply current	30 mA 240 V without extension 40 mA 240 V with extensions 80 mA 100 V without extension 80 mA 100 V with extensions
Discrete input current	0.6 mA
Number or control scheme lines	120 ladder ≤ 200 FBD
Cycle time	6...90 ms
Backup time	10 years 25 °C
Clock drift	6 s/month 25 °C 12 min/year 0...55 °C
Checks	Program memory on each power up
Supply voltage limits	85...264 V
Supply frequency	50/60 Hz
Power consumption in VA	7 VA without extension 12 VA with extensions
Isolation voltage	1780 V
Protection type	Against inversion of terminals (control instructions not executed)
Discrete input voltage	100...240 V AC
Discrete input frequency	47...53 Hz 57...63 Hz
Voltage state 1 guaranteed	≥ 79 V discrete input
Voltage state 0 guaranteed	≤ 40 V discrete input
Current state 1 guaranteed	> 0.17 mA discrete input
Current state 0 guaranteed	< 0.5 mA discrete input
Input impedance	350 kOhm discrete input
Output voltage limits	5...30 V DC relay output 24...250 V AC
Contacts type and composition	NO relay output
Output thermal current	8 A for all 4 outputs relay output
Electrical durability	500000 cycles DC-12 24 V 1.5 A relay output EN/IEC 60947-5-1 500000 cycles DC-13 24 V 0.6 A relay output EN/IEC 60947-5-1 500000 cycles AC-12 230 V 1.5 A relay output EN/IEC 60947-5-1 500000 cycles AC-15 230 V 0.9 A relay output EN/IEC 60947-5-1
Switching capacity in mA	≥ 10 mA 12 V relay output
Operating rate in Hz	0.1 Hz at le relay output 10 Hz no load relay output

Mechanical durability	10000000 cycles relay output
[Uimp] rated impulse withstand voltage	4 kV EN/IEC 60947-1 and EN/IEC 60664-1
Clock	With
Response time	5 ms from state 1 to state 0 relay output 10 ms from state 0 to state 1 relay output 50...255 ms FBD from state 0 to state 1 discrete input 50...255 ms FBD from state 1 to state 0 discrete input 50 ms ladder from state 0 to state 1 discrete input 50 ms ladder from state 1 to state 0 discrete input
Connections - terminals	Screw terminals 1 x 0.25...1 x 2.5 mm ² 24...14 flexible with cable end Screw terminals 2 x 0.25...2 x 0.75 mm ² 24...18 flexible with cable end Screw terminals 1 x 0.2...1 x 2.5 mm ² 25...14 semi-solid Screw terminals 1 x 0.2...1 x 2.5 mm ² 25...14 solid Screw terminals 2 x 0.2...2 x 1.5 mm ² 24...16 solid
Tightening torque	0.5 N.m
Overvoltage category	III EN/IEC 60664-1
Product weight	0.25 kg

Environment

Immunity to microbreaks	≤ 10 ms
Product certifications	C-Tick CSA GL GOST UL
Standards	EN/IEC 60068-2-27 Ea EN/IEC 60068-2-6 Fc EN/IEC 61000-4-11 EN/IEC 61000-4-12 EN/IEC 61000-4-2 level 3 EN/IEC 61000-4-3 EN/IEC 61000-4-4 level 3 EN/IEC 61000-4-5 EN/IEC 61000-4-6 level 3
IP degree of protection	IP20 terminal block IEC 60529 IP40 front panel IEC 60529
Environmental characteristic	EMC directive EN/IEC 61131-2 zone B EMC directive EN/IEC 61000-6-2 EMC directive EN/IEC 61000-6-3 EMC directive EN/IEC 61000-6-4 Low voltage directive EN/IEC 61131-2
Disturbance radiated/conducted	Class B EN 55022-11 group 1
Pollution degree	2 EN/IEC 61131-2
Ambient air temperature for operation	-20...40 °C in non-ventilated enclosure IEC 60068-2-1 and IEC 60068-2-2 -20...55 °C IEC 60068-2-1 and IEC 60068-2-2
Ambient air temperature for storage	-40...70 °C
Operating altitude	2000 m
Altitude transport	≤ 3048 m
Relative humidity	95 % without condensation or dripping water
RoHS EUR conformity date	0622
RoHS EUR status	Compliant