

HMISBC

Rear Module controller panel - Dig 8 inputs/8 outputs +Ana 4 In/2 Out



Main

Commercial Status	Commercialised
Range of product	Magelis SCU
Product or component type	Controller

Complementary

Supply	External source
[Us] rated supply voltage	24 V at 20.4...28.8 V DC
Immunity to microbreaks	<= 10 ms
Inrush current	<= 30 A
Power consumption	15 W
Local signalling	No indicator
Number of pages	Limited by internal memory capacity
Software designation	SoMachine
Operating system	Magelis
Processor name	CPU RISC
Processor frequency	333 MHz
Memory description	128 MB application run memory, type: DRAM 128 kB internal data storage memory, type: FRAM 128 MB flash memory, type: NAND
Integrated connection type	CANopen master bus, connector type: SUB-D 9 1 USB (V2.0) port, connector type: USB A 1 USB (V2.0) port, connector type: mini B USB 1 serial link, communication ports RS485/RS232, connector type: RJ45, transmission rate: <= 115.2 kbits/s 1 Ethernet TCP/IP, connector type: RJ45
Realtime clock	Built-in
Downloadable protocols	Modbus Modbus TCP/IP Third party protocols Uni-TE CANopen
Fixing mode	By 1 nut - diameter: Ø 22 mm, mounting on: 1...6 mm thick panel
Enclosure material	PC/PBT
Shock resistance	294 m/s ² (duration=6 ms) conforming to IEC 60068-2-27 on panel mounting 147 m/s ² (duration=11 ms) conforming to IEC 60068-2-27 on DIN rail
Vibration resistance	1 gn (f=9...150 Hz) conforming to IEC 60068-2-6 +/- 3.5 mm (f=5...9 Hz) conforming to IEC 60068-2-6

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Electromagnetic compatibility	<p>Radiated emission - test level: 30 MHz...1 GHz conforming to EN 55011</p> <p>Conducted emission - test level: 150 kHz...30 MHz conforming to EN 55011</p> <p>Conducted RF disturbances - test level: 10 V, 0.15...80 MHz conforming to IEC 61000-4-6</p> <p>Surge immunity test - test level: 0.5 kV differential mode, digital I/O conforming to IEC 61000-4-5</p> <p>Surge immunity test - test level: 1 kV common mode, digital I/O conforming to IEC 61000-4-5</p> <p>Surge immunity test - test level: 1 kV, power supply (differential mode) conforming to IEC 61000-4-5</p> <p>Surge immunity test - test level: 2 kV, power supply (common mode) conforming to IEC 61000-4-5</p> <p>Electrical fast transient/burst immunity test - test level: 1 kV, CAN line conforming to IEC 61000-4-4</p> <p>Electrical fast transient/burst immunity test - test level: 1 kV, COM line conforming to IEC 61000-4-4</p> <p>Electrical fast transient/burst immunity test - test level: 1 kV, Ethernet line conforming to IEC 61000-4-4</p> <p>Electrical fast transient/burst immunity test - test level: 2 kV, relay wires conforming to IEC 61000-4-4</p> <p>Electrical fast transient/burst immunity test - test level: 1 kV, between analogue I/O and operating voltage conforming to IEC 61000-4-4</p> <p>Electrical fast transient/burst immunity test - test level: 2 kV, power lines conforming to IEC 61000-4-4</p> <p>Susceptibility to electromagnetic fields - test level: 10 V/m, 80 MHz...3 GHz conforming to IEC 61000-4-3</p> <p>Electrostatic discharge immunity test - test level: 6 kV, contact discharge conforming to IEC 61000-4-2</p> <p>Electrostatic discharge immunity test - test level: 8 kV, air discharge conforming to IEC 61000-4-2</p>
Discrete input number	<p>6 for digital input conforming to IEC 61131-2 Type 1</p> <p>2 for fast input (normal mode) conforming to IEC 61131-2 Type 1</p>
Discrete input voltage	24 V DC discrete input logic:sink or source (positive/negative)
Number of common point	<p>1 for digital input</p> <p>1 for fast input (HSC mode)</p>
Discrete input current	<p>5 mA for digital</p> <p>7.83 mA for fast input</p>
Input impedance	<p>4.7 kOhm</p> <p>2.81 kOhm</p>
Sensor power supply	<p>15...28.8 V DC, voltage (state 1): ≥ 15 V, current (state 1): ≥ 2.5 mA, voltage (state 0): ≤ 5 V, current (state 0): ≤ 1 mA</p> <p>15...28.8 V DC, voltage (state 1): ≥ 15 V, current (state 1): ≥ 5 mA, voltage (state 0): ≤ 5 V, current (state 0): ≤ 1.5 mA</p>
Configurable filtering time	<p>3...12 ms integrator (none/run/stop)</p> <p>0.004...0.04 ms bounce filter (latch/event and cumulative filter by step $N \times 0.5$ms ($64 \geq N \geq 2$))</p> <p>0 ms no filter (none)</p>
Input frequency	<p>100 kHz for fast input - control type pulse/direction</p> <p>100 kHz for fast input - control type single phase</p> <p>100 kHz for fast input (encoder mode) - control type A/B</p>
Cable length	<p>50 m unshielded cable for digital input</p> <p>100 m shielded cable for digital input</p> <p>10 m shielded cable for fast input</p>
Connection pitch	3.5 mm
Overvoltage protection	With
Isolation between channels and internal logic	500 V DC
Isolation between channels	None
Discrete output number	<p>6 digital output, output logic: source</p> <p>2 fast output (normal mode), output logic: source</p>
Discrete output voltage	<p>220 V AC (voltage limit: 100...250 V) with relay discrete output(s)</p> <p>24 V DC (voltage limit: 5...30 V) with relay discrete output(s)</p> <p>24 V DC (voltage limit: 19.2...28.8 V) with transistor discrete output(s)</p>
Input/Output number	<p>6 for digital output, terminal(s): DQ0...DQ5</p> <p>6 for digital input, terminal(s): DI0...DI5</p> <p>2 for fast output, terminal(s): FQ0...FQ1</p> <p>2 for fast input, terminal(s): FI0...FI1</p>

Discrete output current	2 A (current per output common:4 A), response time 2 ms with closing contact for digital output 2 A (current per output common:4 A), response time 5 ms with opening contact for digital output 50 mA, response time 2 ms for fast output (PWM or PTO mode) 300 mA, response time 2 ms for fast output (normal mode)
Insulation resistance	> 10 MOhm between power supply and earth > 10 MOhm between the I/O and internal logic
Output frequency	<= 1 kHz for fast output (PWM mode) <= 100 kHz for fast output (PTO mode)
Absolute accuracy error	+/- 15 % of full scale of cyclic ratio 30...70% for fast output (PWM or PTO mode) +/- 10 % of full scale of cyclic ratio 20...80% for fast output (PWM or PTO mode) +/- 5 % of full scale of cyclic ratio 10...90% for fast output (PWM or PTO mode) 1 % of full scale of cyclic ratio 1...99% for fast output (PWM or PTO mode) +/- 0.1 % of full scale of cyclic ratio 1...99% for fast output (PWM or PTO mode)
Analogue input number	2 for RTDs 2 for analog input
Analogue input range	-10...+10 V or 0...10 V - resolution: 12 bits + sign, input impedance: >= 1 MOhm 0...20 mA/4...20 mA - resolution: 12 bits, input impedance: 250 Ohm (tolerance: +/- 1 %)
Analogue input type	RTD at - 200...1300 °C - resolution: 16 bits (thermocouple N) RTD at - 200...900 °C - resolution: 16 bits (thermocouple E) RTD at - 200...400 °C - resolution: 16 bits (thermocouple T) RTD at 0...1600 °C - resolution: 16 bits (thermocouple S) RTD at 200...1800 °C - resolution: 16 bits (thermocouple B) RTD at 0...1600 °C - resolution: 16 bits (thermocouple R) RTD at - 240...1370 °C - resolution: 16 bits (thermocouple K) RTD at - 200...760 °C - resolution: 16 bits (thermocouple J) RTD at - 50...200 °C - resolution: 16 bits temperature probe: Ni 100/Ni 1000 RTD at - 200...600 °C - resolution: 16 bits temperature probe: Pt 100/Pt 1000
Analogue output number	2 resistive load for 12 bits + sign
Analogue output range	-10...10 V/0...10 V (> 2 kOhm) for short-circuit 0...20 mA/4...20 mA (> 300 Ohm) for open-circuit
Height	50.65 mm
Width	5.04 in (128 mm)
Depth	4.02 in (102 mm)
Product weight	0.398 kg

Environment

Standards	EN 61131-2 FCC Class A IEC 61000-6-2 RoHS compliant UL 508 ANSI/ISA 12-12-01 WEEE directive 2002/96/EC CSA C22.2 No 213 Class I Division 2 RoHS China SJ/T 11363-2006
Product certifications	C-Tick CULus 508 GOST CUL 1604 Class 1 Division 2 KCC CULus CSA 22-2 No 142
Marking	CE
Ambient air temperature for operation	32...122 °F (0...50 °C)
Ambient air temperature for storage	-4...140 °F (-20...60 °C)
Relative humidity	5...85 % without condensation
Operating altitude	<= 6561.68 ft (2000 m)
Storage altitude	<= 10000 m
Maximum pressure	800...1114 hPa
IP degree of protection	IP65 for front panel conforming to IEC 60529 IP20 for rear panel conforming to IEC 60529
NEMA degree of protection	NEMA 4X for front panel

Pollution degree	2 conforming to IEC 60664
Environmental characteristic	Corrosive gas free
