

Datasheet

RS Stock No. 1242554

# RS Pro 1/2"NPT External Mount Float Switch with Temperature Sensing



- Compact design with temperature sensing
- 1/2"NPT thread for external mount
- 25VA & 100VA versions
- Float material SS 316, stem material SS 304
- N/O or N/C switching action
- Temperature measurement from -20°C to +120°C

The TSSF212 series is a compact external fitting device, via 1/2"NPT thread, with a high specification thermistor so capable of sensing both liquid level and temperature.

The device does not require access to the inside of the tank.

Application of the product is typically used in the pharmaceutical industry, food and beverage and dairies industry, as well as biofuel industry.

They are manufactured in stainless steel, to suit most commonly used liquids.

The switch action may be reversed by rotating the device through 180°.

### Technical Specification

Mounting Style	External
Mounting Thread	1/2"NPT
Float & Stem Material	SS 316 & SS 304
Maximum Temperature	-20°C to 120°C
Maximum Pressure	10 bar
Float SG	0.7
Minimum Fluid SG	0.8

### Electrical Specification

	25W (Y Code)	100W (H Code)
Contact Form	N/O (N/C)	N/O (N/C)
Switching Power Max	25 VA	100
Switching Voltage AC Max	V 240	300
Switching Voltage DC Max	V 120	300
Switching Current Max	A 0.6	1

### Thermistor Specification

Nominal Temperature Resistance	10k Ohm at 25°C
Resistance Tolerance	+/- 1% (25°C) to +/- 4.3% (120°C)
Operating Temperature Range	-20°C to +120°C
Temperature Sensing Accuracy	+/- 0.2°C (0°C to +70°C)
Beta Value	3892K (0/50°C)
Response Time	<1 sec
Dissipation Constant	0.75mW/K

RS Stock No.	Standard Parts	Temperature	Max Power	Leadouts	Output
1242554	TSSF212H100	-20°C to + 120°C	100VA	100cm XLPE AWG 22	SPNO + Temp
1242553	TSSF212Y100	-20°C to + 120°C	25VA	100cm XLPE AWG 22	SPNO + Temp

### Mechanical Dimensions

