

ISOLATOR 63A TRIPLE POLE+NEUTRAL, RED HANDLE



Figure similar

Model	
Product brand name	SENTRON
Product designation	On/Off switches
Type of light source	Not applicable
Mounting type / for light source	Not applicable
Design of the switching function	Switch disconnecter
General technical data	
Number of poles	3
Number of poles / Note	3P+N
Short-circuit current rating	10 kA
Type of voltage	AC
Protection class	
Protection class IP	Other
Switching capacity	
Switching capacity current / rated value	0.196 kA
Main circuit	

Operating voltage / rated value	440 V
Operating current / rated value	63 A

### Appearance

Color / of the lens	Not applicable
---------------------	----------------

### Product details

Product component / Signal lamp	No
---------------------------------	----

### Product function

Product function / positive opening (acc. to DIN VDE 0113)	No
--	----

### Number

Number of NC contacts	0
Number of NO contacts	3
Number of CO contacts	0

### Mechanical Design

Height	89.8 mm
Depth	74.5 mm
Installation depth	70 mm
Number of width units	4

#### General Product Approval

#### Declaration of Conformity



### Further information

#### Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

#### Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5TL1663-1>

#### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5TL1663-1>

#### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=5TL1663-1](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5TL1663-1)

#### CAX-Online-Generator

<http://www.siemens.com/cax>

#### Tender specifications

<http://www.siemens.com/specifications>