

SIMATIC S7-1200, CPU 1215C, compact CPU, AC/DC/relay, 2 PROFINET ports, onboard I/O: 14 DI 24 V DC; 10 DO relay 2 A, 2 AI 0-10 V DC, 2 AO 0-20 mA DC, Power supply: AC 85-264 V AC at 47-63 Hz, Program/data memory 125 KB



General information	
Product type designation	CPU 1215C AC/DC/relay
Firmware version	V4.2
Engineering with	
<ul style="list-style-type: none"> <li>Programming package</li> </ul>	STEP 7 V14 or higher
Supply voltage	
Rated value (AC)	
<ul style="list-style-type: none"> <li>120 V AC</li> </ul>	Yes
<ul style="list-style-type: none"> <li>230 V AC</li> </ul>	Yes
permissible range, lower limit (AC)	85 V
permissible range, upper limit (AC)	265 V
Line frequency	
<ul style="list-style-type: none"> <li>permissible range, lower limit</li> </ul>	47 Hz
<ul style="list-style-type: none"> <li>permissible range, upper limit</li> </ul>	63 Hz
Input current	
Current consumption (rated value)	100 mA at 120 V AC; 50 mA at 240 V AC
Current consumption, max.	300 mA at 120 V AC; 150 mA at 240 V AC
Inrush current, max.	20 A; at 264 V

I <sup>2</sup> t	0.8 A <sup>2</sup> ·s
<b>Output current</b>	
for backplane bus (5 V DC), max.	1 600 mA; Max. 5 V DC for SM and CM
<b>Encoder supply</b>	
24 V encoder supply	
• 24 V	20.4 to 28.8V
<b>Power loss</b>	
Power loss, typ.	14 W
<b>Memory</b>	
Work memory	
• integrated	125 kbyte
• expandable	No
Load memory	
• integrated	4 Mbyte
• Plug-in (SIMATIC Memory Card), max.	with SIMATIC memory card
Backup	
• present	Yes
• maintenance-free	Yes
• without battery	Yes
<b>CPU processing times</b>	
for bit operations, typ.	0.08 µs; / instruction
for word operations, typ.	1.7 µs; / instruction
for floating point arithmetic, typ.	2.3 µs; / instruction
<b>CPU-blocks</b>	
Number of blocks (total)	DBs, FCs, FBs, counters and timers. The maximum number of addressable blocks ranges from 1 to 65535. There is no restriction, the entire working memory can be used
OB	
• Number, max.	Limited only by RAM for code
<b>Data areas and their retentivity</b>	
Retentive data area (incl. timers, counters, flags), max.	10 kbyte
Flag	
• Number, max.	8 kbyte; Size of bit memory address area
Local data	
• per priority class, max.	16 kbyte; Priority class 1 (program cycle): 16 KB, priority class 2 to 26: 6 KB
<b>Address area</b>	
Process image	
• Inputs, adjustable	1 kbyte

- Outputs, adjustable

1 kbyte

## Hardware configuration

Number of modules per system, max. 3 comm. modules, 1 signal board, 8 signal modules

## Time of day

### Clock

- Hardware clock (real-time) Yes
- Backup time 480 h; Typical
- Deviation per day, max.  $\pm 60$  s/month at 25 °C

## Digital inputs

Number of digital inputs 14; Integrated  
 • of which inputs usable for technological functions 6; HSC (High Speed Counting)

Source/sink input Yes

### Number of simultaneously controllable inputs

all mounting positions

— up to 40 °C, max. 14

### Input voltage

- Rated value (DC) 24 V
- for signal "0" 5 V DC at 1 mA
- for signal "1" 15 V DC at 2.5 mA

### Input delay (for rated value of input voltage)

for standard inputs

- parameterizable Yes; 0.2 ms, 0.4 ms, 0.8 ms, 1.6 ms, 3.2 ms, 6.4 ms and 12.8 ms, selectable in groups of four
- at "0" to "1", min. 0.2 ms
- at "0" to "1", max. 12.8 ms

for interrupt inputs

- parameterizable Yes

for counter/technological functions

- parameterizable Single phase: 3 @ 100 kHz & 3 @ 30 kHz, differential: 3 @ 80 kHz & 3 @ 30 kHz

### Cable length

- shielded, max. 500 m; 50 m for technological functions
- unshielded, max. 300 m; For technological functions: No

## Digital outputs

Number of digital outputs 10; Relays

### Switching capacity of the outputs

- with resistive load, max. 2 A
- on lamp load, max. 30 W with DC, 200 W with AC

### Output delay with resistive load

- "0" to "1", max. 10 ms; max.

• "1" to "0", max.	10 ms; max.
<b>Relay outputs</b>	
• Number of operating cycles, max.	mechanically 10 million, at rated load voltage 100 000
<b>Cable length</b>	
• shielded, max.	500 m
• unshielded, max.	150 m
<b>Analog inputs</b>	
Number of analog inputs	2
<b>Input ranges</b>	
• Voltage	Yes
<b>Input ranges (rated values), voltages</b>	
• 0 to +10 V	Yes
• Input resistance (0 to 10 V)	≥100k ohms
<b>Cable length</b>	
• shielded, max.	100 m; twisted and shielded
<b>Analog outputs</b>	
Number of analog outputs	2
<b>Output ranges, current</b>	
• 0 to 20 mA	Yes
<b>Analog value generation for the inputs</b>	
<b>Integration and conversion time/resolution per channel</b>	
• Resolution with overrange (bit including sign), max.	10 bit
• Integration time, parameterizable	Yes
• Conversion time (per channel)	625 μs
<b>Encoder</b>	
<b>Connectable encoders</b>	
• 2-wire sensor	Yes
<b>1. Interface</b>	
Interface type	PROFINET
Physics	Ethernet
Isolated	Yes
automatic detection of transmission rate	Yes
Autonegotiation	Yes
Autocrossing	Yes
<b>Interface types</b>	
• Number of ports	2
• integrated switch	Yes
<b>Functionality</b>	
• PROFINET IO Controller	Yes

• PROFINET IO Device	Yes
• SIMATIC communication	Yes
• Open IE communication	Yes
• Web server	Yes
• Media redundancy	Yes; as MRP client
<b>PROFINET IO Controller</b>	
• Transmission rate, max.	100 Mbit/s
<b>Services</b>	
— PG/OP communication	Yes
— S7 routing	Yes
— Isochronous mode	No
— Open IE communication	Yes
— IRT	No
— MRP	Yes; as MRP client
— MRPD	No
— PROFINergy	No
— Prioritized startup	Yes
— Number of IO devices with prioritized startup, max.	16
— Number of connectable IO Devices, max.	16
— Number of connectable IO Devices for RT, max.	16
— of which in line, max.	16
— Activation/deactivation of IO Devices	Yes
— Number of IO Devices that can be simultaneously activated/deactivated, max.	8
— Updating time	The minimum value of the update time also depends on the communication component set for PROFINET IO, on the number of IO devices and the quantity of configured user data.
<b>PROFINET IO Device</b>	
<b>Services</b>	
— PG/OP communication	Yes
— S7 routing	Yes
— Isochronous mode	No
— Open IE communication	Yes
— IRT	No
— MRP	Yes; as MRP client
— MRPD	No
— PROFINergy	Yes
— Shared device	Yes
— Number of IO Controllers with shared device, max.	2

Protocols	
Supports protocol for PROFINET IO	Yes
PROFIBUS	Yes; CM 1243-5 required
AS-Interface	Yes; CM 1243-2 required
Protocols (Ethernet)	
• TCP/IP	Yes
• DHCP	No
• SNMP	Yes
• DCP	Yes
• LLDP	Yes
Open IE communication	
• TCP/IP	Yes
— Data length, max.	8 kbyte
• ISO-on-TCP (RFC1006)	Yes
— Data length, max.	8 kbyte
• UDP	Yes
— Data length, max.	1 472 byte
Web server	
• User-defined websites	Yes
Further protocols	
• MODBUS	Yes
Communication functions	
S7 communication	
• supported	Yes
• as server	Yes
• as client	Yes
• User data per job, max.	See online help (S7 communication, user data size)
Web server	
• supported	Yes
Number of connections	
• overall	16; dynamically
Test commissioning functions	
Status/control	
• Status/control variable	Yes
• Variables	Inputs/outputs, memory bits, DBs, distributed I/Os, timers, counters
Forcing	
• Forcing	Yes
Diagnostic buffer	
• present	Yes
Traces	

- Number of configurable Traces 2
- Memory size per trace, max. 512 kbyte

### Interrupts/diagnostics/status information

#### Diagnostics indication LED

- RUN/STOP LED Yes
- ERROR LED Yes
- MAINT LED Yes

### Integrated Functions

Number of counters	6
Counting frequency (counter) max.	100 kHz
Frequency measurement	Yes
controlled positioning	Yes
Number of position-controlled positioning axes, max.	8
Number of positioning axes via pulse-direction interface	Up to 4 with SB 1222
PID controller	Yes
Number of alarm inputs	4

### Potential separation

#### Potential separation digital inputs

- Potential separation digital inputs 500V AC for 1 minute
- between the channels, in groups of 1

#### Potential separation digital outputs

- Potential separation digital outputs Relays
- between the channels No
- between the channels, in groups of 2

### EMC

#### Interference immunity against discharge of static electricity

- Interference immunity against discharge of static electricity acc. to IEC 61000-4-2 Yes
  - Test voltage at air discharge 8 kV
  - Test voltage at contact discharge 6 kV

#### Interference immunity to cable-borne interference

- Interference immunity on supply lines acc. to IEC 61000-4-4 Yes
- Interference immunity on signal cables acc. to IEC 61000-4-4 Yes

#### Interference immunity against voltage surge

- on the supply lines acc. to IEC 61000-4-5 Yes

#### Interference immunity against conducted variable disturbance induced by high-frequency fields

- Interference immunity against high-frequency radiation acc. to IEC 61000-4-6 Yes

<b>Emission of radio interference acc. to EN 55 011</b>	
<ul style="list-style-type: none"> <li>• Limit class A, for use in industrial areas</li> <li>• Limit class B, for use in residential areas</li> </ul>	<p>Yes; Group 1</p> <p>Yes; When appropriate measures are used to ensure compliance with the limits for Class B according to EN 55011</p>
<b>Degree and class of protection</b>	
Degree of protection acc. to EN 60529	
<ul style="list-style-type: none"> <li>• IP20</li> </ul>	Yes
<b>Standards, approvals, certificates</b>	
CE mark	Yes
UL approval	Yes
cULus	Yes
FM approval	Yes
RCM (formerly C-TICK)	Yes
KC approval	Yes
Marine approval	Yes
<b>Ambient conditions</b>	
Free fall	
<ul style="list-style-type: none"> <li>• Fall height, max.</li> </ul>	0.3 m; five times, in product package
Ambient temperature during operation	
<ul style="list-style-type: none"> <li>• min.</li> <li>• max.</li> <li>• horizontal installation, min.</li> <li>• horizontal installation, max.</li> <li>• vertical installation, min.</li> <li>• vertical installation, max.</li> </ul>	<p>-20 °C</p> <p>60 °C; Number of simultaneously activated inputs or outputs 7 or 5 (no adjacent points) at 60 °C horizontal or 50 °C vertical, 14 or 10 at 55 °C horizontal or 45 °C vertical</p> <p>-20 °C</p> <p>60 °C</p> <p>-20 °C</p> <p>50 °C</p>
Ambient temperature during storage/transportation	
<ul style="list-style-type: none"> <li>• min.</li> <li>• max.</li> </ul>	<p>-40 °C</p> <p>70 °C</p>
Air pressure acc. to IEC 60068-2-13	
<ul style="list-style-type: none"> <li>• Operation, min.</li> <li>• Operation, max.</li> <li>• Storage/transport, min.</li> <li>• Storage/transport, max.</li> </ul>	<p>795 hPa</p> <p>1 080 hPa</p> <p>660 hPa</p> <p>1 080 hPa</p>
Altitude during operation relating to sea level	
<ul style="list-style-type: none"> <li>• Installation altitude, min.</li> <li>• Installation altitude, max.</li> </ul>	<p>-1 000 m</p> <p>2 000 m</p>
Relative humidity	
<ul style="list-style-type: none"> <li>• Operation, max.</li> </ul>	95 %; no condensation
Vibrations	



<ul style="list-style-type: none"> <li>• Vibration resistance during operation acc. to IEC 60068-2-6</li> <li>• Operation, tested according to IEC 60068-2-6</li> </ul>	2 g (m/s <sup>2</sup> ) wall mounting, 1 g (m/s <sup>2</sup> ) DIN rail Yes
<b>Shock testing</b>	
<ul style="list-style-type: none"> <li>• tested according to IEC 60068-2-27</li> </ul>	Yes; IEC 68, Part 2-27 half-sine: strength of the shock 15 g (peak value), duration 11 ms
<b>Pollutant concentrations</b>	
<ul style="list-style-type: none"> <li>• SO2 at RH &lt; 60% without condensation</li> </ul>	SO2: < 0.5 ppm; H2S: < 0.1 ppm; RH < 60% condensation-free
<b>Configuration</b>	
<b>Programming</b>	
<b>Programming language</b>	
— LAD	Yes
— FBD	Yes
— SCL	Yes
<b>Know-how protection</b>	
<ul style="list-style-type: none"> <li>• User program protection/password protection</li> <li>• Copy protection</li> <li>• Block protection</li> </ul>	Yes Yes Yes
<b>Access protection</b>	
<ul style="list-style-type: none"> <li>• Protection level: Write protection</li> <li>• Protection level: Read/write protection</li> <li>• Protection level: Complete protection</li> </ul>	Yes Yes Yes
<b>Cycle time monitoring</b>	
<ul style="list-style-type: none"> <li>• adjustable</li> </ul>	Yes
<b>Dimensions</b>	
Width	130 mm
Height	100 mm
Depth	75 mm
<b>Weights</b>	
Weight, approx.	550 g
<b>last modified:</b>	04/13/2018