




Datasheet

Stock No: 188-0316

92mm Square Flange Mount SPDT Float Switch



- 92 x 92 mm Square Flange mount
- SS 316L float material
- SS 304 other wetted parts material
- Aluminium enclosure with lid and cable gland connection

The S35 series are 92mm square flange mount float operated level switches. This design uses a pivoted float arm with a magnet on the inboard end. This magnet when moved by the rising float arm interacts with another magnet in the switch enclosure to give a snap action operation.

Technical Specification

Mounting style External via flange Mounting size 92 x 92 mm square Float material 316L grade SS Other wetted parts SS 304 Operating Temperature 0 - 130°C M20 x 1.5 Cable entry Maximum pressure 19bar@20°C, 15bar@130°C* **Enclosure rating** IP68 Nitrile Minimum fluid SG Sealing gasket Switch differential +/- 10mm from centreline

Electrical Specification

- to be confirmed


SPCO (changeover) Contact Form

Switching Voltage AC Max V Switching Voltage DC Max V

Switching Current Max 4 (resistive load) 3 (inductive load)


Stocking No.

188-0316



NC (Red) CO(Yellow) NO (Blue)

NO (Normally Open) is made on a falling level NC (Normally Closed) is made on a rising level



S35 RS Pro 2019



Specifications are subject to change without prior notice.