

PRODUCT-DETAILS

MSHD-LY

MSHD-LY Handles



General Information

| | |
|-----------------------|---|
| Extended Product Type | MSHD-LY |
| Product ID | 1SAM201920R1002 |
| EAN | 4013614441837 |
| Catalog Description | MSHD-LY Handles |
| Long Description | MSHD-LY Handle, IP64, red/yellow, 3 times lockable, defeatable, 0-I Suitable for Manual Motor Starter |

Ordering

| | |
|------------------------|----------|
| Minimum Order Quantity | 1 piece |
| Customs Tariff Number | 85389099 |

Popular Downloads

| | |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | 1SBC100173C0201 |
| Instructions and Manuals | 2CDC131033M6801 |

Dimensions

| | |
|--------------------|---------|
| Product Net Width | 65.6 mm |
| Product Net Height | 65.5 mm |

| | |
|----------------------------|----------|
| Product Net Depth / Length | 57.9 mm |
| Product Net Weight | 0.065 kg |

Technical

| | |
|-----------------------------|---|
| Contact Position Indication | ON / OFF |
| Actuator Type | Rotary Handle |
| Shaft Diameter | 6x6 mm |
| Color | Yellow / Red |
| Degree of Protection | IP64 |
| Tightening Torque | 0.12 N·m |
| Product Name | Handles |
| Suitable For | MS116 MS132 MO132 MS450 MS451 MS495 MS496 MS497 MO450 MO495 MO496 |
| Suitable for Product Class | Manual Motor Starter |
| Accessory Group | Mechanical |
| Accessory Type | Handles |

Technical UL/CSA

| | |
|--------------------------|---------------|
| Enclosure Type UL/CSA | 1 12 3R |
| Tightening Torque UL/CSA | 1.06 in·lb |

Environmental

| | |
|-------------|---|
| RoHS Status | Following EU Directive 2002/95/EC August 18, 2005 and amendment |
|-------------|---|

Certificates and Declarations (Document Number)

| | |
|----------------------------------|---|
| Declaration of Conformity - CE | 1SAD938504-0196 1SAD938506-0197 1SAD938508-0188 1SAD938509-0183 1SAD938516-0125 |
| Declaration of Conformity - UKCA | 1SAD938500-1060;1SAD938500-1003;1SAD938500-1037 |
| Instructions and Manuals | 2CDC131033M6801 |
| RoHS Information | 1SAD938504-0196 1SAD938506-0197 1SAD938508-0188 1SAD938509-0183 1SAD938516-0125 |

Container Information

| | |
|--------------------------------|---------------|
| Package Level 1 Width | 130 mm |
| Package Level 1 Depth / Length | 70 mm |
| Package Level 1 Height | 170 mm |
| Package Level 1 Gross Weight | 0.1 kg |
| Package Level 1 EAN | 4013614441837 |
| Package Level 1 Units | 1 piece |

Classifications

| | |
|------------------------------------|--|
| Object Classification Code | X |
| ETIM 4 | EC002498 - Accessories for low-voltage switch technology |
| ETIM 5 | EC000229 - Handle for power circuit breaker |
| ETIM 6 | EC000229 - Handle for power circuit breaker |
| ETIM 7 | EC000229 - Handle for power circuit breaker |
| eClass | V11.0 : 27370414 |
| UNSPSC | 39121521 |
| IDEA Granular Category Code (IGCC) | 3038 >> Handles or knobs |
| E-Number (Finland) | 3705865 |
| E-Number (Sweden) | 3112089 |

Accessories

| Identifier | Description | Type | Quantity | Unit Of Measure |
|-----------------|---|----------|----------|-----------------|
| 1SAM201920R1000 | MSH-AR Salvamotori e relè termici | MSH-AR | 1 | piece |
| 1SAM101923R0002 | MSMN Salvamotori e relè termici | MSMN | 1 | piece |
| 1SAM101923R0012 | MSMNO Salvamotori e relè termici | MSMNO | 1 | piece |
| 1SCA101647R1001 | OXS6X85 Albero 6 mm per manovra rotativa, 85 mm | OXS6X85 | 1 | piece |
| 1SCA108043R1001 | OXS6X105 Albero 6 mm per manovra rotativa, 105 mm | OXS6X105 | 1 | piece |
| 1SCA101655R1001 | OXS6X130 Albero 6 mm per manovra rotativa, 130 mm | OXS6X130 | 1 | piece |
| 1SCA101659R1001 | OXS6X180 Albero 6 mm per manovra rotativa, 180 mm | OXS6X180 | 1 | piece |

Categories

Low Voltage Products and Systems → Control Products → Manual Motor Starters → Manual Motor Starters Accessories

