

# Coupling unit CM-IVN

For expansion of the insulation monitoring relay CM-IWN.x measuring range up to  $U_n = 690 \text{ V AC}$  and  $1000 \text{ V DC}$

The CM-IVN serves to extend the measuring range of the insulation monitoring relay CM-IWN.x for monitoring the insulation resistance up to  $690 \text{ V AC}$  and  $1000 \text{ V DC}$  in accordance with IEC 61557-8.

The CM-IVN is available with two different terminal versions. You can choose between the proven screw connection technology (double-chamber cage connection terminals) and the completely tool-free Easy Connect Technology (push-in terminals).

## Characteristics

- Expansion of the nominal voltage range of the insulation monitoring relay CM-IWN.x for monitoring the insulation resistance of unearthened IT systems up to  $690 \text{ V AC}$  and  $1000 \text{ V DC}$
- According to IEC/EN 61557-8 "Electrical safety in low voltage distribution systems up to  $1000 \text{ V a.c.}$  and  $1500 \text{ V d.c.}$  – Equipment for testing, measuring or monitoring of protective measures – Part 8: Insulation monitoring devices for IT systems"
- Passive device, no supply voltage needed
- Screw connection technology or Easy Connect Technology available
- Housing material for highest fire protection classification UL 94 V-0
- Tool-free mounting on DIN rail as well as demounting
- $45 \text{ mm}$  ( $1.77 \text{ in}$ ) width


## Order data

### Coupling unit

Type	Nominal voltage $U_n$ of the distribution system to be monitored	Rated control supply voltage	Connection technology	Order code
CM-IVN.P	0-690 V AC / 0-1000 V DC	Passive device, no control supply voltage needed	Push-in terminals	1SVR 760 669 R9400
CM-IVN.S			Screw type terminals	1SVR 750 669 R9400

### Accessories

Type	Description	Order code
ADP.02	Adapter for screw mounting	1SVR 440 029 R0100
MAR.01	Marker label	1SVR 366 017 R0100
COV.12	Sealable transparent cover	1SVR 750 005 R0100



## Approvals

- UL 508, CAN/CSA C22.2 No. 14
- GL
- IEC/EN 60947-5-1, CB scheme
- GB14048.5 - 2001, CCC
- GOST

## Marks

- CE
- C-Tick

## Functions

### Application / monitoring function

The coupling unit CM-IVN is designed to extend the nominal voltage range of the insulation monitoring relay CM-IWN.x up to 690 V AC and 1000 V DC. The coupling unit can be connected to the system to be monitored by means of the terminals VL+ and VL-. The terminal V⊥ has to be connected to the earth potential. The terminals L+, V1+, L-, V1-, VS and VE have to be connected to the CM-IWN.x as shown in the connection diagrams below.

Supply systems with voltages  $U_n = 0-690 \text{ V AC (15-400 Hz)}$  or  $0-1000 \text{ V DC}$  can be connected.

### Measuring principle


With CM-IWN.x a pulsating measuring signal is fed into the system to be monitored and the insulation resistance calculated.

This pulsating measuring signal alters its form depending on the insulation resistance and system leakage capacitance. From this altered form the change in the insulation resistance is forecast.

When the forecast insulation resistance corresponds to the insulation resistance calculated in the next measurement cycle and is smaller than the set threshold value, the output relays are activated or deactivated, depending on the device configuration. This measuring principle is also suitable for the detection of symmetrical insulation faults.

## Connection and wiring


### Connection diagram




## Wiring diagrams

Always connect L+ and L- to different conductors. L+ and L- can be connected to any of the conductors.


$U_n \leq 690$  V AC; 1000 V DC




2-wire AC system




2-wire DC system



3-wire AC system



3-wire DC system



4-wire AC system

## Technical data

Data at  $T_a = 25\text{ °C}$  and rated values, unless otherwise indicated

### Input circuits

Input circuit - Measuring circuit	VL+, VL-, V $\perp$	
Function	expansion of the nominal voltage range of the insulation monitoring relay CM-IWN.x to 690 V AC or 1000 V DC, max. length of connection cable 40 cm	
Measuring principle	see CM-IWN.x	
Nominal voltage $U_n$ of the distribution system to be monitored	0-690 V AC / 0-1000 V DC	
Voltage range of the distribution system to be monitored	0-793.5 V AC / 0-1150 V DC (tolerance +15 %)	
Rated frequency $f_N$ of the distribution system to be monitored	DC or 15-400 Hz	
Tolerance of the rated frequency $f_N$	13.5-440 Hz	
System leakage capacitance $C_e$	max.	identical to that of the insulation monitoring relay used
Extraneous DC voltage $U_{fg}$ (when connected to an AC system)	max.	793.5 V DC
Tolerance of the adjusted threshold value / Relative percentage uncertainty A	at 1-15 k $\Omega$ $R_F$	$\pm 1.5\%$
	at 15-200 k $\Omega$ $R_F$	$\pm 8\%$
at $-5...+45\text{ °C}$ , $U_n = 0-115\%$ , $U_s = 85-110\%$ , $f_N, f_s, C_e = 1\mu\text{F}$		
Internal impedance $Z_i$	at 50 Hz	195 k $\Omega$
Internal DC resistance $R_i$		200 k $\Omega$
Measuring voltage $U_m$		24 V
Tolerance of measuring voltage $U_m$		+10 %
Measuring current $I_m$		0.15 mA

### General data

MTBF	on request	
Duty time	100 %	
Dimensions (W x H x D)	45 x 78 x 100 mm (1.78 x 3.07 x 3.94 in)	
Weight	net weight	<b>Screw connection technology</b> 0.179 kg (0.395 lb)
	gross weight	<b>Easy Connect Technology (push-in)</b> 0.165 kg (0.364 lb)
Mounting	DIN rail (IEC/EN 60715), snap-on mounting without any tool	
	any	
Mounting position	any	
Minimum distance to other units	not necessary	
Degree of protection	10 mm (0.39 in) at $U_n > 400\text{ V}$	
	housing / terminal	IP50 / IP20

### Electrical connection

		Screw connection technology	Easy Connect Technology (push-in)
Wire size	fine-strand with(out) wire end ferrule	1 x 0.5-2.5 mm <sup>2</sup> (1 x 20-14 AWG), 2 x 0.5-1.5 mm <sup>2</sup> (2 x 20-16 AWG)	2 x 0.5-1.5 mm <sup>2</sup> (2 x 20-16 AWG)
	rigid	1 x 0.5-4 mm <sup>2</sup> , (1 x 20-12 AWG), 2 x 0.5-2.5 mm <sup>2</sup> (2 x 20-14 AWG)	2 x 0.5-1.5 mm <sup>2</sup> (2 x 20-16 AWG)
Stripping length		8 mm (0.32 in)	
Tightening torque		0.6 - 0.8 Nm (5.31 - 7.08 lb.in)	-
Max. length of connection cable to CM-IWN.x		40 cm	

## Environmental data

Ambient temperature ranges	operation	-25...+60 °C
	storage	-40...+85 °C
	transport	-40...+85 °C
Climatic category	IEC/EN 60721-3-3	3K5 (no condensation, no ice formation)
Damp heat, cyclic	IEC/EN 60068-2-30	6 x 24 h cycle, 55 °C, 95 % RH
Vibration, sinusoidal	IEC/EN 60255-21-1	Class 2
Shock, half-sine	IEC/EN 60255-21-2	Class 2

## Isolation data

Rated impulse withstand voltage $U_{imp}$ (IEC/EN 60947-1, IEC/EN 60664-1)	input circuit / PE	8 kV
Pollution degree (IEC/EN 60664-1)		3
Overvoltage category (IEC/EN 60664-1)		III
Rated insulation voltage $U_i$ (IEC/EN 60947-1, IEC/EN 60664-1)	input circuit / PE	1000 V
Test voltage, routine test (IEC/EN 60255-5, IEC/EN 61010-1)	input circuit / PE	3.3 kV, 50 Hz, 1 s

## Standards


Product standard	IEC/EN 61557-8, IEC/EN 60255-6
Other standards	EN 50178
Low Voltage Directive	2006/95/EC
EMC Directive	2004/108/EC
RoHS Directive	2002/95/EC

## Electromagnetic compatibility

Interference immunity to		IEC/EN 61000-6-1, IEC/EN 61000-6-2, IEC/EN 61326-2-4
electrostatic discharge	IEC/EN 61000-4-2	Level 3, 6 kV / 8 kV
radiated, radio-frequency, electromagnetic field	IEC/EN 61000-4-3	Level 3, 10 V/m (1 GHz) / 3 V/m (2 GHz) / 1 V/m (2.7 GHz)
electrical fast transient/burst	IEC/EN 61000-4-4	Level 3, 2 kV / 5 kHz
surge	IEC/EN 61000-4-5	Level 3, installation class 3, supply circuit and measuring circuit 1 kV L-L, 2 kV L-earth
conducted disturbances, induced by radio-frequency fields	IEC/EN 61000-4-6	Level 3, 10 V
voltage dips, short interruptions and voltage variations	IEC/EN 61000-4-11	Class 3
harmonics and interharmonics	IEC/EN 61000-4-13	Class 3
Interference emission		IEC/EN 61000-6-3, IEC/EN 61000-6-4
high-frequency radiated	IEC/CISPR 22, EN 55022	Class B
high-frequency conducted	IEC/CISPR 22, EN 55022	Class B


## Dimensions

in **mm** and *inches*




## Accessories


in **mm** and *inches*



**ADP.02** - Adapter for screw mounting



**MAR.12** - Marker label for devices with DIP switches



**COV.12** - Sealable transparent cover

## Further documentation

Document title	Document type	Document number
Electronic products and relays	Catalog	2CDC 110 004 C020x
CM-IWN.1, CM-IWN.4, CM-IWN.5, CM-IWN.6	Instruction sheet	1SVC 750 020 M0000

You can find the documentation on the internet at [www.abb.com/lowvoltage](http://www.abb.com/lowvoltage) -> Control Products -> Electronic Relays and Controls -> Insulation Monitors.

# Contact us

## **ABB STOTZ-KONTAKT GmbH**

P. O. Box 10 16 80  
69006 Heidelberg, Germany  
Phone: +49 (0) 6221 7 01-0  
Fax: +49 (0) 6221 7 01-13 25  
E-mail: info.desto@de.abb.com

You can find the address of your  
local sales organisation on the  
ABB home page  
<http://www.abb.com/contacts>  
-> Low Voltage Products and Systems

### **Note:**

We reserve the right to make technical changes or modify the contents of this document without prior notice. With regard to purchase orders, the agreed particulars shall prevail. ABB AG does not accept any responsibility whatsoever for potential errors or possible lack of information in this document.

We reserve all rights in this document and in the subject matter and illustrations contained therein. Any reproduction, disclosure to third parties or utilization of its contents – in whole or in parts – is forbidden without prior written consent of ABB AG.

Copyright© 2012 ABB  
All rights reserved