



### Main

Range	PowerLogic
Product name	CT
Product or component type	Current transformer
Secondary current	5 A
Accuracy class	Class 0.5 at 20 VA Class 1 at 25 VA
[In] rated current	2000 A

### Complementary

Current transformer type	Tropicalised for busbar
Current transformer ratio	2000/5
[I <sub>th</sub> ] conventional free air thermal current	60 kA
Dynamic withstand current	2.5 I <sub>th</sub>
Maximum safety factor	5
[U <sub>e</sub> ] rated operational voltage	< 720 V AC 50/60 Hz
[U <sub>i</sub> ] rated insulation voltage	3 kV
Mounting mode	Insulated locking screw
Mounting support	Busbar
Width	98 mm outside: 40 mm inner:
Height	129 mm outside: 103 mm inner:
Depth	40 mm frame: 75 mm total:
Net weight	0.656 kg
[U <sub>imp</sub> ] rated impulse withstand voltage	3 kV
Electrical insulation class	Class B
Opening of bars	102 x 38

Sealing	With
---------	------

## Environment

Standards	VDE 0414 IEC 61869-2
Product certifications	CE
IP degree of protection	IP20
Relative humidity	0...95 %
Ambient air temperature for operation	-25...50 °C

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End of Life Information</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins