

**Datasheet**


# RS PRO Acoustic and Luminous Warning Device

Stock No: 199-9745



## Technical Specifications:

<b>CUPOLA</b> DOME DOME HAUBE CÚPULA	PC
<b>BASE</b> BASE BASE SOCKET BASE	PC/ABS
<b>GUARNIZIONE</b> GASKET JOINT DICHTUNG JUNTA	O-Ring EPDM

<b>COLORI DISPONIBILI</b> AVAILABLE COLOURS COULEURS DISPONIBLES VERFÜGBARE FARBEN COLORES DISPONIBLES									
<b>VOLTAGGIO</b> VOLTAGE TENSION SPANNUNG TENSIÓN	12Vdc – 24Vdc – 240Vac								
<b>SERVIZIO</b> OPERATION FONCTIONNEMENT BETRIEBSART FUNCIONAMIENTO	T: ON = 1min. OFF = 10min.								
<b>CORRENTE NOMINALE</b> CURRENT CONSUMPTION CONSOMMATION DE COURANT STROMAUFNAHME CONSUMO DE CORRIENTE	<table border="1" data-bbox="721 502 1249 569"> <thead> <tr> <th></th> <th>12Vdc</th> <th>24Vdc</th> <th>240Vac</th> </tr> </thead> <tbody> <tr> <td>mA (Max)</td> <td>75</td> <td>65</td> <td>50</td> </tr> </tbody> </table>		12Vdc	24Vdc	240Vac	mA (Max)	75	65	50
	12Vdc	24Vdc	240Vac						
mA (Max)	75	65	50						
<b>RESA ACUSTICA</b> ACOUSTIC OUTPUT RENDEMENT ACOUSTIQUE SCHALLLEISTUNGSPEGEL SALIDA ACUSTICA	<table border="1" data-bbox="721 625 1249 693"> <thead> <tr> <th></th> <th>12Vdc</th> <th>24Vdc</th> <th>240Vac</th> </tr> </thead> <tbody> <tr> <td>dB(A)1m</td> <td>96</td> <td>96</td> <td>92</td> </tr> </tbody> </table>		12Vdc	24Vdc	240Vac	dB(A)1m	96	96	92
	12Vdc	24Vdc	240Vac						
dB(A)1m	96	96	92						
<b>GRADO IP</b> IP RATING DEGRE IP SCHUTZART GRADO IP	IP43								
<b>TEMPERATURA DI FUNZIONAMENTO</b> OPERATING TEMPERATURE TEMPERATURE DE SERVICE BETRIEBSTEMPERATUR TEMPERATURA DE FUNCIONAMIENTO	-30°C+50°C								
<b>CERTIFICAZIONI, OMOLOGAZIONI</b> CERTIFICATIONS, APPROVALS CERTIFICATIONS, HOMOLOGATIONS PRODUKTZERTIFIKATE, ZULASSUNGEN CERTIFICADOS, HOMOLOGACIONES	CE								
<b>FISSAGGIO</b> MOUNTING FIXATION FIXIERUNG FIJACIÓN	Viti Screws Vis Schrauben Tornillos								
<b>DISEGNO</b> TECHNICAL DRAWING DESSIN TECHNISCHE ZEICHNUNG DIBUJO TECNICO	