

Product type designation

CM 1542-1

Communication module CM 1542-1 for connection of S7-1500 to PROFINET as IO controller: TCP/IP, ISO-on-TCP, UDP, S7 communication, IP broadcast Multicast, SNMPV1, time-of-day synchronization via NTP, 2xRJ45 (10/100 Mbit)



Transfer rate	
Transfer rate	
<ul style="list-style-type: none"> at the 1st interface 	10 ... 100 Mbit/s
Interfaces	
Number of interfaces / acc. to Industrial Ethernet	1
Number of electrical connections	
<ul style="list-style-type: none"> at the 1st interface / acc. to Industrial Ethernet 	2
Type of electrical connection	
<ul style="list-style-type: none"> at the 1st interface / acc. to Industrial Ethernet 	RJ45 port
Supply voltage, current consumption, power loss	
Type of voltage / of the supply voltage	DC
Supply voltage / 1 / from backplane bus	15 V
Relative symmetrical tolerance / at DC	
<ul style="list-style-type: none"> at 15 V 	3 %
Consumed current	
<ul style="list-style-type: none"> from backplane bus / at DC / at 15 V / typical 	0.22 A
Power loss [W]	3.3 W

Ambient conditions

Ambient temperature	
• for vertical installation / during operation	0 ... 40 °C
• for horizontally arranged busbars / during operation	0 ... 60 °C
• during storage	-40 ... +70 °C
• during transport	-40 ... +70 °C
Relative humidity	
• at 25 °C / without condensation / during operation / maximum	95 %
Protection class IP	IP20

Design, dimensions and weights

Module format	Compact module S7-1500 single width
Width	35 mm
Height	142 mm
Depth	129 mm
Net weight	0.4 kg
Mounting type	
• S7-1500 rail mounting	Yes

Product features, product functions, product components / general

Number of units	
• per CPU / maximum	8
• Note	depending on CPU type

Performance data / open communication

Number of possible connections / for open communication	
• by means of T blocks / maximum	64; depending on the system upper limit
Amount of data	
• as user data per ISO on TCP connection / for open communication / by means of T blocks / maximum	65536 byte
Number of Multicast stations	6

Performance data / S7 communication

Number of possible connections / for S7 communication	
• maximum	64; depending on the system upper limit

Performance data / multi-protocol mode

Number of active connections / with multi-protocol mode	64
---	----

Performance data / PROFINET communication / as PN IO controller

Product function / PROFINET IO controller	Yes
---	-----

Number of PN IO devices / on PROFINET IO controller / usable / total	128
Number of PN IO IRT devices / on PROFINET IO controller / usable	64
Number of external PN IO lines / with PROFINET / per rack	10
Amount of data	
<ul style="list-style-type: none"> • as user data for input variables / as PROFINET IO controller / maximum 	8 Kibyte
<ul style="list-style-type: none"> • as user data for input variables / as PROFINET IO controller / maximum 	8 Kibyte
<ul style="list-style-type: none"> • as user data for input variables per PN IO device / as PROFINET IO controller / maximum 	1433 byte
<ul style="list-style-type: none"> • as user data for output variables per PN IO device / as PROFINET IO controller / maximum 	1433 byte
<ul style="list-style-type: none"> • as user data for input variables per PN IO device / for each sub-module as PROFINET IO controller / maximum 	256 byte
<ul style="list-style-type: none"> • as user data for output variables per PN IO device / for each sub-module as PROFINET IO controller / maximum 	256 byte

Performance data / PROFINET communication / as PN IO device

Product function / PROFINET IO device	Yes
Amount of data	
<ul style="list-style-type: none"> • as user data for input variables / as PROFINET IO device / maximum 	8192 byte
<ul style="list-style-type: none"> • as user data for input variables / as PROFINET IO device / maximum 	8192 byte
<ul style="list-style-type: none"> • as user data for input variables / for each sub-module as PROFINET IO device 	256 byte
<ul style="list-style-type: none"> • as user data for input variables / for each sub-module as PROFINET IO device 	256 byte
<ul style="list-style-type: none"> • as user data for the consistency area for each sub-module 	256 byte
Number of submodules / per PROFINET IO-Device	32

Performance data / telecontrol

Protocol / is supported	
<ul style="list-style-type: none"> • TCP/IP 	Yes

Product functions / management, configuration, engineering

Product function / MIB support	Yes
Protocol / is supported	
<ul style="list-style-type: none"> • SNMP v1 	Yes
<ul style="list-style-type: none"> • DCP 	Yes
<ul style="list-style-type: none"> • LLDP 	Yes

Configuration software	
<ul style="list-style-type: none"> • required 	STEP 7 Professional V14 (TIA Portal) or higher
Identification & maintenance function	
<ul style="list-style-type: none"> • I&M0 - device-specific information 	Yes
<ul style="list-style-type: none"> • I&M1 – higher-level designation/location designation 	Yes

Product functions / Diagnostics

Product function / Web-based diagnostics	Yes; via S7-1500 CPU
--	----------------------

Product functions / Switch

Product feature / Switch	Yes
Product function	
<ul style="list-style-type: none"> • switch-managed 	No
<ul style="list-style-type: none"> • with IRT / PROFINET IO switch 	Yes
<ul style="list-style-type: none"> • Configuration with STEP 7 	Yes

Product functions / Routing

Service / Routing / Note	IP routing up to 1 Mbps
Product function	
<ul style="list-style-type: none"> • Static IP routing 	Yes
<ul style="list-style-type: none"> • Static IP routing IPv6 	No
<ul style="list-style-type: none"> • dynamic IP routing 	No
<ul style="list-style-type: none"> • dynamic IP routing IPv6 	No
Protocol / is supported	
<ul style="list-style-type: none"> • RIP v1 	No
<ul style="list-style-type: none"> • RIPv2 	No
<ul style="list-style-type: none"> • RIPnG for IPv6 	No
<ul style="list-style-type: none"> • OSPFv2 	No
<ul style="list-style-type: none"> • OSPFv3 for IPv6 	No
<ul style="list-style-type: none"> • VRRP 	No
<ul style="list-style-type: none"> • VRRP for IPv6 	No
<ul style="list-style-type: none"> • BGP 	No
<ul style="list-style-type: none"> • PPP 	No
<ul style="list-style-type: none"> • PpOE via DSL 	No

Product functions / redundancy

Product function	
<ul style="list-style-type: none"> • Ring redundancy 	Yes
<ul style="list-style-type: none"> • Redundancy manager 	Yes
Protocol / is supported / Media Redundancy Protocol (MRP)	Yes

Product functions / Security

Product function	
------------------	--

- switch-off of non-required services
- Blocking of communication via physical ports
- log file for unauthorized access

Yes
No
No

Product functions / time

Product function / SICLOCK support	Yes
Product function / pass on time synchronization	Yes
Protocol / is supported	
• NTP	Yes

Further information / Internet-Links

Internet-Link	
• to website: Selector SIMATIC NET SELECTION TOOL	http://www.siemens.com/snst
• to website: Industrial communication	http://www.siemens.com/simatic-net
• to website: Industry Mall	https://mall.industry.siemens.com
• to website: Information and Download Center	http://www.siemens.com/industry/infocenter
• to website: Image database	http://automation.siemens.com/bilddb
• to website: CAx Download Manager	http://www.siemens.com/cax
• to website: Industry Online Support	https://support.industry.siemens.com

Security information

Security information	Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit http://www.siemens.com/industrialsecurity . To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit http://support.automation.siemens.com . (V3.4)
----------------------	---

last modified:

05/12/2020