



SIMATIC S7-1500 Analog input/output module AI 4x U/I/R/RTD/TC ST; 4 channels in groups of 4; Hardware interrupts; Diagnostics AQ 2x U/I ST; 2 channels in groups of 2; Substitute value; Diagnostics Common mode voltage approx. 10 V 16 bit; Accuracy 0.3%; Delivery including push-in front connector, infeed element, shield bracket and shield terminal

General information	
Product type designation	AI 4xU/I/RTD/TC /AQ 2xU/I ST
HW functional status	FS01
Firmware version	V1.0.0
<ul style="list-style-type: none"> <li>FW update possible</li> </ul>	Yes
Product function	
<ul style="list-style-type: none"> <li>I&amp;M data</li> </ul>	Yes; I&M0 to I&M3
<ul style="list-style-type: none"> <li>Prioritized startup</li> </ul>	No
<ul style="list-style-type: none"> <li>Measuring range scalable</li> </ul>	No
<ul style="list-style-type: none"> <li>Scalable measured values</li> </ul>	No
<ul style="list-style-type: none"> <li>Adjustment of measuring range</li> </ul>	No
<ul style="list-style-type: none"> <li>Output range scalable</li> </ul>	No
Engineering with	
<ul style="list-style-type: none"> <li>STEP 7 TIA Portal configurable/integrated as of version</li> </ul>	V13 / V13.0.2
<ul style="list-style-type: none"> <li>STEP 7 configurable/integrated as of version</li> </ul>	V5.5 SP3 / -
<ul style="list-style-type: none"> <li>PROFIBUS as of GSD version/GSD revision</li> </ul>	V1.0 / V5.1
<ul style="list-style-type: none"> <li>PROFINET as of GSD version/GSD revision</li> </ul>	V2.3 / -
Operating mode	

• Oversampling	No
• MSI	Yes
• MSO	Yes

#### CiR – Configuration in RUN

Reparameterization possible in RUN	Yes
Calibration possible in RUN	Yes

#### Supply voltage

Type of supply voltage	DC
Rated value (DC)	24 V
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes

#### Input current

Current consumption, max.	200 mA; with 24 V DC supply
---------------------------	-----------------------------

#### Encoder supply

24 V encoder supply	
• Short-circuit protection	Yes
• Output current, max.	20 mA; Max. 47 mA per channel for a duration < 10 s

#### Power

Power available from the backplane bus	0.7 W
--	-------

#### Power loss

Power loss, typ.	3.3 W
------------------	-------

#### Analog inputs

Number of analog inputs	4
• For current measurement	4
• For voltage measurement	4
• For resistance/resistance thermometer measurement	2
• For thermocouple measurement	4
permissible input voltage for voltage input (destruction limit), max.	28.8 V
permissible input current for current input (destruction limit), max.	40 mA
Technical unit for temperature measurement adjustable	Yes; °C/°F/K
Analog input with oversampling	No
Standardization of measured values	No
Input ranges (rated values), voltages	
• 0 to +5 V	No
• 0 to +10 V	No

• 1 V to 5 V — Input resistance (1 V to 5 V)	Yes 100 kΩ
• -1 V to +1 V — Input resistance (-1 V to +1 V)	Yes 10 MΩ
• -10 V to +10 V — Input resistance (-10 V to +10 V)	Yes 100 kΩ
• -2.5 V to +2.5 V — Input resistance (-2.5 V to +2.5 V)	Yes 10 MΩ
• -25 mV to +25 mV	No
• -250 mV to +250 mV — Input resistance (-250 mV to +250 mV)	Yes 10 MΩ
• -5 V to +5 V — Input resistance (-5 V to +5 V)	Yes 100 kΩ
• -50 mV to +50 mV — Input resistance (-50 mV to +50 mV)	Yes 10 MΩ
• -500 mV to +500 mV — Input resistance (-500 mV to +500 mV)	Yes 10 MΩ
• -80 mV to +80 mV — Input resistance (-80 mV to +80 mV)	Yes 10 MΩ

#### Input ranges (rated values), currents

• 0 to 20 mA — Input resistance (0 to 20 mA)	Yes 25 Ω; Plus approx. 42 ohms for overvoltage protection by PTC
• -20 mA to +20 mA — Input resistance (-20 mA to +20 mA)	Yes 25 Ω; Plus approx. 42 ohms for overvoltage protection by PTC
• 4 mA to 20 mA — Input resistance (4 mA to 20 mA)	Yes 25 Ω; Plus approx. 42 ohms for overvoltage protection by PTC

#### Input ranges (rated values), thermocouples

• Type B — Input resistance (Type B)	Yes 10 MΩ
• Type C	No
• Type E — Input resistance (Type E)	Yes 10 MΩ
• Type J — Input resistance (type J)	Yes 10 MΩ
• Type K — Input resistance (Type K)	Yes 10 MΩ
• Type L	No
• Type N — Input resistance (Type N)	Yes 10 MΩ
• Type R — Input resistance (Type R)	Yes 10 MΩ

- Type S
  - Input resistance (Type S)
- Type T
  - Input resistance (Type T)
- Type U
- Type TXK/TXK(L) to GOST

Yes  
10 MΩ  
Yes  
10 MΩ  
No  
No

Input ranges (rated values), resistance thermometer

- Cu 10
- Cu 10 according to GOST
- Cu 50
- Cu 50 according to GOST
- Cu 100
- Cu 100 according to GOST
- Ni 10
- Ni 10 according to GOST
- Ni 100
  - Input resistance (Ni 100)
- Ni 100 according to GOST
- Ni 1000
  - Input resistance (Ni 1000)
- Ni 1000 according to GOST
- LG-Ni 1000
  - Input resistance (LG-Ni 1000)
- Ni 120
- Ni 120 according to GOST
- Ni 200
- Ni 200 according to GOST
- Ni 500
- Ni 500 according to GOST
- Pt 10
- Pt 10 according to GOST
- Pt 50
- Pt 50 according to GOST
- Pt 100
  - Input resistance (Pt 100)
- Pt 100 according to GOST
- Pt 1000
  - Input resistance (Pt 1000)
- Pt 1000 according to GOST
- Pt 200
  - Input resistance (Pt 200)

No  
No  
No  
No  
No  
No  
No  
No  
Yes; Standard/climate  
10 MΩ  
No  
Yes; Standard/climate  
10 MΩ  
No  
Yes; Standard/climate  
10 MΩ  
No  
No  
No  
No  
No  
No  
No  
No  
No  
No  
Yes; Standard/climate  
10 MΩ  
No  
Yes; Standard/climate  
10 MΩ  
No  
Yes; Standard/climate  
10 MΩ

• Pt 200 according to GOST	No
• Pt 500	Yes; Standard/climate
— Input resistance (Pt 500)	10 MΩ
• Pt 500 according to GOST	No
<b>Input ranges (rated values), resistors</b>	
• 0 to 150 ohms	Yes
— Input resistance (0 to 150 ohms)	10 MΩ
• 0 to 300 ohms	Yes
— Input resistance (0 to 300 ohms)	10 MΩ
• 0 to 600 ohms	Yes
— Input resistance (0 to 600 ohms)	10 MΩ
• 0 to 3000 ohms	No
• 0 to 6000 ohms	Yes
— Input resistance (0 to 6000 ohms)	10 MΩ
• PTC	Yes
— Input resistance (PTC)	10 MΩ
<b>Thermocouple (TC)</b>	
<b>Temperature compensation</b>	
— parameterizable	Yes
— internal temperature compensation	Yes
— external temperature compensation via RTD	Yes
— Compensation for 0 °C reference point temperature	Yes; fixed value can be set
— Reference channel of the module	No
<b>Cable length</b>	
• shielded, max.	800 m; for U/I, 200 m for R/RTD, 50 m for TC
<b>Analog outputs</b>	
Number of analog outputs	2
Voltage output, short-circuit protection	Yes
Voltage output, short-circuit current, max.	24 mA
Current output, no-load voltage, max.	22 V
Cycle time (all channels), min.	3.2 ms; ±0.5 ms, regardless of the number of activated channels
<b>Output ranges, voltage</b>	
• 0 to 10 V	Yes
• 1 V to 5 V	Yes
• -5 V to +5 V	No
• -10 V to +10 V	Yes
<b>Output ranges, current</b>	
• 0 to 20 mA	Yes
• -20 mA to +20 mA	Yes
• 4 mA to 20 mA	Yes

Connection of actuators	
• for voltage output two-wire connection	Yes
• for voltage output four-wire connection	Yes
• for current output two-wire connection	Yes
Load impedance (in rated range of output)	
• with voltage outputs, min.	1 k $\Omega$ ; 0.5 k $\Omega$ at 1 to 5 V
• with voltage outputs, capacitive load, max.	1 $\mu$ F
• with current outputs, max.	750 $\Omega$
• with current outputs, inductive load, max.	10 mH
Cable length	
• shielded, max.	800 m; for current, 200 m for voltage
Analog value generation for the inputs	
Integration and conversion time/resolution per channel	
• Resolution with overrange (bit including sign), max.	16 bit
• Integration time, parameterizable	Yes
• Integration time (ms)	2,5 / 16,67 / 20 / 100 ms
• Basic conversion time, including integration time (ms)	9 / 23 / 27 / 107 ms
— additional conversion time for wire-break monitoring	9 ms
— additional conversion time for resistance measurement	150 ohm, 300 ohm, 600 ohm, Pt100, Pt200, Ni100: 2 ms, 6000 ohm, Pt500, Pt1000, Ni1000, LG-Ni1000, PTC: 4 ms
• Interference voltage suppression for interference frequency f1 in Hz	400 / 60 / 50 / 10
• Time for offset calibration (per module)	Basic conversion time of the slowest channel
Smoothing of measured values	
• parameterizable	Yes
• Step: None	Yes
• Step: low	Yes
• Step: Medium	Yes
• Step: High	Yes
Analog value generation for the outputs	
Integration and conversion time/resolution per channel	
• Resolution with overrange (bit including sign), max.	16 bit
• Conversion time (per channel)	0.5 ms
Settling time	
• for resistive load	1.5 ms
• for capacitive load	2.5 ms
• for inductive load	2.5 ms

## Encoder

Connection of signal encoders	
• for voltage measurement	Yes
• for current measurement as 2-wire transducer — Burden of 2-wire transmitter, max.	Yes 820 $\Omega$
• for current measurement as 4-wire transducer	Yes
• for resistance measurement with two-wire connection	Yes; Only for PTC
• for resistance measurement with three-wire connection	Yes; All measuring ranges except PTC; internal compensation of the cable resistances
• for resistance measurement with four-wire connection	Yes; All measuring ranges except PTC

## Errors/accuracies

Linearity error (relative to input range), (+/-)	0.02 %
Temperature error (relative to input range), (+/-)	0.005 %/K; With TC type T 0.02 $\pm$ % / K
Crosstalk between the inputs, max.	-80 dB
Repeat accuracy in steady state at 25 °C (relative to input range), (+/-)	0.02 %
Output ripple (relative to output range, bandwidth 0 to 50 kHz), (+/-)	0.02 %
Linearity error (relative to output range), (+/-)	0.15 %
Temperature error (relative to output range), (+/-)	0.002 %/K
Crosstalk between the outputs, max.	-100 dB
Repeat accuracy in steady state at 25 °C (relative to output range), (+/-)	0.05 %
Temperature error of internal compensation	$\pm 6$ °C

## Operational error limit in overall temperature range

• Voltage, relative to input range, (+/-)	0.3 %
• Current, relative to input range, (+/-)	0.3 %
• Resistance, relative to input range, (+/-)	0.3 %
• Resistance thermometer, relative to input range, (+/-)	0.3 %; Ptxxx standard: $\pm 1.5$ K, Ptxxx climate: $\pm 0.5$ K, Nixxx standard: $\pm 0.5$ K, Nixxx climate: $\pm 0.3$ K
• Thermocouple, relative to input range, (+/-)	0.3 %; Type B: $> 600$ °C $\pm 4.6$ K, type E: $> -200$ °C $\pm 1.5$ K, type J: $> -210$ °C $\pm 1.9$ K, type K: $> -200$ °C $\pm 2.4$ K, type N: $> -200$ °C $\pm 2.9$ K, type R: $> 0$ °C $\pm 4.7$ K, type S: $> 0$ °C $\pm 4.6$ K, type T: $> -200$ °C $\pm 2.4$ K
• Voltage, relative to output range, (+/-)	0.3 %
• Current, relative to output range, (+/-)	0.3 %

## Basic error limit (operational limit at 25 °C)

• Voltage, relative to input range, (+/-)	0.1 %
• Current, relative to input range, (+/-)	0.1 %
• Resistance, relative to input range, (+/-)	0.1 %

<ul style="list-style-type: none"> <li>Resistance thermometer, relative to input range, (+/-)</li> <li>Thermocouple, relative to input range, (+/-)</li> </ul>	0.1 %; Ptxxx standard: $\pm 0.7$ K, Ptxxx climate: $\pm 0.2$ K, Nixxx standard: $\pm 0.3$ K, Nixxx climate: $\pm 0.15$ K  0.1 %; Type B: $> 600$ °C $\pm 1.7$ K, type E: $> -200$ °C $\pm 0.7$ K, type J: $> -210$ °C $\pm 0.8$ K, type K: $> -200$ °C $\pm 1.2$ K, type N: $> -200$ °C $\pm 1.2$ K, type R: $> 0$ °C $\pm 1.9$ K, type S: $> 0$ °C $\pm 1.9$ K, type T: $> -200$ °C $\pm 0.8$ K
<ul style="list-style-type: none"> <li>Voltage, relative to output range, (+/-)</li> <li>Current, relative to output range, (+/-)</li> </ul>	0.2 % 0.2 %
<b>Interference voltage suppression for <math>f = n \times (f_1 \pm 1 \%)</math>, <math>f_1</math> = interference frequency</b>	
<ul style="list-style-type: none"> <li>Series mode interference (peak value of interference &lt; rated value of input range), min.</li> <li>Common mode voltage, max.</li> <li>Common mode interference, min.</li> </ul>	40 dB 10 V 60 dB
<b>Isochronous mode</b>	
Isochronous operation (application synchronized up to terminal)	No
<b>Interrupts/diagnostics/status information</b>	
Diagnostics function	Yes
Substitute values connectable	Yes
<b>Alarms</b>	
<ul style="list-style-type: none"> <li>Diagnostic alarm</li> <li>Limit value alarm</li> </ul>	Yes Yes; two upper and two lower limit values in each case
<b>Diagnostic messages</b>	
<ul style="list-style-type: none"> <li>Monitoring the supply voltage</li> <li>Wire-break</li> <li>Short-circuit</li> <li>Overflow/underflow</li> </ul>	Yes Yes; only for input type 1 ... 5 V, 4 ... 20 mA, TC, R, RTD and output type current Yes; Only for output type "voltage" Yes
<b>Diagnostics indication LED</b>	
<ul style="list-style-type: none"> <li>RUN LED</li> <li>ERROR LED</li> <li>Monitoring of the supply voltage (PWR-LED)</li> <li>Channel status display</li> <li>for channel diagnostics</li> <li>for module diagnostics</li> </ul>	Yes; green LED Yes; red LED Yes; green LED Yes; green LED Yes; red LED Yes; red LED
<b>Potential separation</b>	
<b>Potential separation analog inputs</b>	
<ul style="list-style-type: none"> <li>between the channels</li> <li>between the channels, in groups of</li> <li>between the channels and backplane bus</li> <li>Between the channels and load voltage L+</li> </ul>	No 4 Yes Yes
<b>Potential separation analog outputs</b>	



- |  |     |
|--|-----|
| • between the channels                     | No  |
| • between the channels, in groups of       | 2   |
| • between the channels and backplane bus   | Yes |
| • Between the channels and load voltage L+ | Yes |

### Permissible potential difference

between S- and MANA (UCM)	8 V DC
---------------------------	--------

### Isolation

Isolation tested with	707 V DC (type test)
-----------------------	----------------------

### Ambient conditions

#### Ambient temperature during operation

- |                                 |       |
|---------------------------------|-------|
| • horizontal installation, min. | 0 °C  |
| • horizontal installation, max. | 60 °C |
| • vertical installation, min.   | 0 °C  |
| • vertical installation, max.   | 40 °C |

#### Altitude during operation relating to sea level

- |   |  |
|---|--|
| • Installation altitude above sea level, max. | 5 000 m; Restrictions for installation altitudes > 2 000 m, see manual |
|---|--|

### Dimensions

Width	25 mm
Height	147 mm
Depth	129 mm

### Weights

Weight, approx.	250 g
-----------------	-------

### Other

Note:	Supplied incl. 40-pole push-in front connectors. Additional basic error and noise for integration time = 2.5 ms: Voltage: $\pm 250$ mV ( $\pm 0.02\%$ ), $\pm 80$ mV ( $\pm 0.05\%$ ), $\pm 50$ mV ( $\pm 0.05\%$ ); resistance: 150 Ohms ( $\pm 0.02\%$ ); resistance thermometer: Pt100 climate: $\pm 0.08$ K, Ni100 climate: $\pm 0.08$ K; thermoelement: Type B, R, S: $\pm 3$ K, type E, J, K, N, T: $\pm 1$ K
-------	---

last modified:	04/10/2020
----------------	------------