

SIMATIC DP, Power module for Electronic modules ET 200 PRO
PM-E, 24 V DC, incl. bus module, connection module PM-E
6ES7194-4B.00-0AA0 order separately



Supply voltage

Load voltage 2L+

- | | |
|-------------------------------|---|
| • Rated value (DC) | 24 V |
| • Short-circuit protection | Yes; via an exchangeable fuse in the power module |
| • Reverse polarity protection | Yes; against destruction |

Input current

from load voltage 2L+, max.	3 mA
-----------------------------	------

Current carrying capacity

max.	10 A; up to 55 °C (on the internal busbars of the ET 200pro)
------	--

Power loss

Power loss, typ.	0.1 W
------------------	-------

Interrupts/diagnostics/status information

Diagnostics function	Yes
----------------------	-----

Diagnostic messages

- | | |
|-----------------------------------|-----|
| • Diagnostic information readable | Yes |
| • missing load voltage | Yes |

Diagnostics indication LED

• Group error SF (red)	Yes
• Load voltage monitoring 24 V DC (green)	Yes
Parameter	
missing load voltage	Potential group of the power module
Potential separation	
between load voltage and backplane bus	Yes
Isolation	
Isolation tested with	707 V DC (type test)
Degree and class of protection	
IP degree of protection	IP65/67
Dimensions	
Width	45 mm
Height	130 mm
Depth	35 mm
Weights	
Weight, approx.	140 g
last modified:	05/13/2020