

SIMATIC ET 200SP, BusAdapter BA-SEND BA1XFC, 1x  
FastConnect connection for ET connection



## General information

|                          |              |
|--------------------------|--------------|
| Product type designation | BA-Send 1xFC |
| HW functional status     | From FS05    |

## Interfaces

|                                   |   |
|-----------------------------------|---|
| Supports protocol for PROFINET IO |   |
| Cable length                      |   |
| — Cu conductors                   | 15 m; from IM firmware V3.3: between BA-send and the first ET-CONNECTION bus node and between all other bus nodes |

|                                      |     |
|--------------------------------------|-----|
| ET-Connection                        |     |
| • Number of interfaces ET connection | 1   |
| • FC (FastConnect)                   | Yes |

## Ambient conditions

|   |        |
|---|--------|
| Ambient temperature during operation            |        |
| • horizontal installation, min.                 | -30 °C |
| • horizontal installation, max.                 | 60 °C  |
| • vertical installation, min.                   | -30 °C |
| • vertical installation, max.                   | 50 °C  |
| Altitude during operation relating to sea level |        |

- Installation altitude above sea level, max.

2 000 m; On request: Installation altitudes greater than 2 000 m

#### Dimensions

Width 20 mm

#### Weights

Weight, approx. 44 g

**last modified:** 05/09/2020