

SIMATIC DP, Electronics module 2 AI I High Feature for ET 200S, 15 mm width, Cycle time per module: 0.5 ms, +/-20mA; 15 bit+sign, 4..20mA; 15 bit, Operational limit +/-0.1% with SF LED (group fault)



Supply voltage	
Load voltage L+	
• Rated value (DC)	24 V
• Reverse polarity protection	Yes
Input current	
from load voltage L+ (without load), max.	48 mA
from backplane bus 3.3 V DC, max.	10 mA
Output voltage	
Power supply to the transmitters	
• present	Yes
Power loss	
Power loss, typ.	1.2 W
Address area	
Address space per module	
• Address space per module, max.	4 byte
Analog inputs	
Number of analog inputs	2

permissible input current for current input (destruction limit), max.	50 mA
Cycle time (all channels) max.	0.5 ms; 0.5 ms for 2 channels without noise suppression, 18 / 21 ms per channel with noise suppression
Input ranges (rated values), currents	
• -20 mA to +20 mA	Yes
• 4 mA to 20 mA	Yes
Cable length	
• shielded, max.	200 m
Analog value generation for the inputs	
Integration and conversion time/resolution per channel	
• Resolution with overrange (bit including sign), max.	16 bit
• Interference voltage suppression for interference frequency f1 in Hz	60 / 50 Hz / no
• Conversion time (per channel)	0.04 ms; Without noise suppression 17/20 ms per channel with error
Errors/accuracies	
Operational error limit in overall temperature range	
• Current, relative to input range, (+/-)	0.1 %; 0.2% without interference frequency suppression
Basic error limit (operational limit at 25 °C)	
• Current, relative to input range, (+/-)	0.05 %; 0.1% without interference frequency suppression
Interrupts/diagnostics/status information	
Alarms	
• Hardware interrupt	Yes
Diagnostic messages	
• Wire-break	Yes; Measuring range 4 to 20 mA only
• Group error	Yes
• Overflow/underflow	Yes
Diagnostics indication LED	
• Group error SF (red)	Yes
Parameter	
Remark	12 bytes, 4 bytes in compatibility mode
Diagnostics wire break	Disable / enable
Measurement type/range	deactivated / ±20 mA / 4 to 20 mA
Group diagnostics	Disable / enable
Overflow/underflow	Disable / enable
Potential separation	
Potential separation analog inputs	
• between the channels	No; however, increased permissible potential difference between the inputs.

- between the channels and backplane bus
- Between the channels and load voltage L+

Yes

Yes

Dimensions

Width	15 mm
Height	81 mm
Depth	52 mm

Weights

Weight, approx.	45 g
-----------------	------

last modified: 05/13/2020