

SIMATIC ET 200SP, Analog output module, AQ 2x U/I High Speed, suitable for BU type A0, A1, Color code CC00, channel diagnostics, 16 bit, +/-0.2%



General information	
Product type designation	AQ 2xU/I HS
HW functional status	From FS06
usable BaseUnits	BU type A0, A1
Color code for module-specific color identification plate	CC00
Product function	
<ul style="list-style-type: none"> <li>I&amp;M data</li> </ul>	Yes; I&M0 to I&M3
Engineering with	
<ul style="list-style-type: none"> <li>STEP 7 TIA Portal configurable/integrated as of version</li> </ul>	V13 SP1
<ul style="list-style-type: none"> <li>STEP 7 configurable/integrated as of version</li> </ul>	V5.5 SP3 / -
<ul style="list-style-type: none"> <li>PROFIBUS as of GSD version/GSD revision</li> </ul>	GSD Revision 5
<ul style="list-style-type: none"> <li>PROFINET as of GSD version/GSD revision</li> </ul>	GSDML V2.3
Operating mode	
<ul style="list-style-type: none"> <li>Oversampling</li> </ul>	Yes; 2 channels per module
<ul style="list-style-type: none"> <li>MSO</li> </ul>	No
CiR – Configuration in RUN	
Reparameterization possible in RUN	Yes

Calibration possible in RUN	No
<b>Supply voltage</b>	
Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes
<b>Input current</b>	
Current consumption (rated value)	45 mA; without load
<b>Power loss</b>	
Power loss, typ.	0.9 W
<b>Address area</b>	
Address space per module	
<ul style="list-style-type: none"> <li>Address space per module, max.</li> </ul>	4 byte; + 1 byte for QI information (32 bytes in the oversampling operating mode)
<b>Analog outputs</b>	
Number of analog outputs	2
Voltage output, short-circuit protection	Yes
Voltage output, short-circuit current, max.	45 mA
Cycle time (all channels), min.	125 $\mu$ s
Analog output with oversampling	Yes
<ul style="list-style-type: none"> <li>Values per cycle, max.</li> <li>Resolution, min.</li> </ul>	16 45 $\mu$ s; (2 channels), 35 $\mu$ s (1 channel)
<b>Output ranges, voltage</b>	
<ul style="list-style-type: none"> <li>0 to 10 V</li> <li>1 V to 5 V</li> <li>-5 V to +5 V</li> <li>-10 V to +10 V</li> </ul>	Yes; 15 bit Yes; 13 bit Yes; 15 bit incl. sign Yes; 16 bit incl. sign
<b>Output ranges, current</b>	
<ul style="list-style-type: none"> <li>0 to 20 mA</li> <li>-20 mA to +20 mA</li> <li>4 mA to 20 mA</li> </ul>	Yes; 15 bit Yes; 16 bit incl. sign Yes; 14 bit
<b>Connection of actuators</b>	
<ul style="list-style-type: none"> <li>for voltage output two-wire connection</li> <li>for voltage output four-wire connection</li> <li>for current output two-wire connection</li> </ul>	Yes Yes Yes
<b>Load impedance (in rated range of output)</b>	
<ul style="list-style-type: none"> <li>with voltage outputs, min.</li> <li>with voltage outputs, capacitive load, max.</li> <li>with current outputs, max.</li> <li>with current outputs, inductive load, max.</li> </ul>	2 k $\Omega$ 1 $\mu$ F 500 $\Omega$ 1 mH

Destruction limits against externally applied voltages and currents	
• Voltages at the outputs	30 V
Cable length	
• shielded, max.	1 000 m; 200 m for voltage output
Analog value generation for the outputs	
Integration and conversion time/resolution per channel	
• Resolution with overrange (bit including sign), max.	16 bit
Settling time	
• for resistive load	0.05 ms
• for capacitive load	0.05 ms; Max. 47 nF and 20 m cable length
• for inductive load	0.05 ms
Errors/accuracies	
Output ripple (relative to output range, bandwidth 0 to 50 kHz), (+/-)	0.02 %
Linearity error (relative to output range), (+/-)	0.03 %
Temperature error (relative to output range), (+/-)	0.003 %/K
Crosstalk between the outputs, max.	-50 dB
Repeat accuracy in steady state at 25 °C (relative to output range), (+/-)	0.03 %
Operational error limit in overall temperature range	
• Voltage, relative to output range, (+/-)	0.2 %
• Current, relative to output range, (+/-)	0.2 %
Basic error limit (operational limit at 25 °C)	
• Voltage, relative to output range, (+/-)	0.1 %
• Current, relative to output range, (+/-)	0.1 %
Isochronous mode	
Execution and activation time (TCO), min.	70 µs
Bus cycle time (TDP), min.	125 µs
Interrupts/diagnostics/status information	
Diagnostics function	Yes
Substitute values connectable	Yes
Alarms	
• Diagnostic alarm	Yes
Diagnostic messages	
• Monitoring the supply voltage	Yes
• Wire-break	Yes; channel-by-channel, only for output type "current"
• Short-circuit	Yes; channel-by-channel, only for output type "voltage"
• Group error	Yes
• Overflow/underflow	Yes
Diagnostics indication LED	

- |  |                         |
|--|-------------------------|
| • Monitoring of the supply voltage (PWR-LED) | Yes; green PWR LED      |
| • Channel status display                     | Yes; green LED          |
| • for channel diagnostics                    | Yes; red LED            |
| • for module diagnostics                     | Yes; green/red DIAG LED |

### Potential separation

#### Potential separation channels

- |  |     |
|--|-----|
| • between the channels   | No  |
| • between the channels and backplane bus                       | Yes |
| • between the channels and the power supply of the electronics | Yes |

### Isolation

Isolation tested with	707 V DC (type test)
-----------------------	----------------------

### Ambient conditions

#### Ambient temperature during operation

- |                                 |        |
|---------------------------------|--------|
| • horizontal installation, min. | -30 °C |
| • horizontal installation, max. | 60 °C  |
| • vertical installation, min.   | -30 °C |
| • vertical installation, max.   | 50 °C  |

#### Altitude during operation relating to sea level

- |   |  |
|---|--|
| • Installation altitude above sea level, max. | 2 000 m; On request: Installation altitudes greater than 2 000 m |
|---|--|

### Dimensions

Width	15 mm
Height	73 mm
Depth	58 mm

### Weights

Weight, approx.	31 g
-----------------	------

<b>last modified:</b>	05/13/2020
-----------------------	------------