

SIMATIC ET 200SP, Analog output module, AQ 2x U/I High Feature suitable for BU type A0, A1, Color code CC00, channel diagnostics, 16 bit, +/-0.1%



| General information   |                   |
|---|-------------------|
| Product type designation  | AQ 2xU/I HF       |
| HW functional status  | from FS04         |
| usable BaseUnits  | BU type A0, A1    |
| Color code for module-specific color identification plate   | CC00              |
| Product function  |                   |
| <ul style="list-style-type: none"> <li>I&amp;M data</li> </ul>  | Yes; I&M0 to I&M3 |
| Engineering with  |                   |
| <ul style="list-style-type: none"> <li>STEP 7 TIA Portal configurable/integrated as of version</li> </ul> | V13 / V13         |
| <ul style="list-style-type: none"> <li>STEP 7 configurable/integrated as of version</li> </ul>            | V5.5 SP3 / -      |
| <ul style="list-style-type: none"> <li>PCS 7 configurable/integrated as of version</li> </ul>             | V8.1 SP1          |
| <ul style="list-style-type: none"> <li>PROFIBUS as of GSD version/GSD revision</li> </ul>                 | GSD Revision 5    |
| <ul style="list-style-type: none"> <li>PROFINET as of GSD version/GSD revision</li> </ul>                 | GSDML V2.3        |
| Operating mode  |                   |
| <ul style="list-style-type: none"> <li>Oversampling</li> </ul>  | No                |
| <ul style="list-style-type: none"> <li>MSO</li> </ul>   | No                |

## CiR – Configuration in RUN

|                                    |     |
|------------------------------------|-----|
| Reparameterization possible in RUN | Yes |
| Calibration possible in RUN        | Yes |

## Supply voltage

|                                     |        |
|-------------------------------------|--------|
| Rated value (DC)                    | 24 V   |
| permissible range, lower limit (DC) | 19.2 V |
| permissible range, upper limit (DC) | 28.8 V |
| Reverse polarity protection         | Yes    |

## Input current

|                                   |  |
|-----------------------------------|--|
| Current consumption (rated value) | 45 mA; without load                    |
| Current consumption, max.         | 90 mA; 2 channels current output 20 mA |

## Power loss

|                  |       |
|------------------|-------|
| Power loss, typ. | 0.9 W |
|------------------|-------|

## Address area

### Address space per module

- Address space per module, max. 4 byte; + 1 byte for QI information

## Analog outputs

|   |             |
|---|-------------|
| Number of analog outputs                    | 2           |
| Voltage output, short-circuit protection    | Yes         |
| Voltage output, short-circuit current, max. | 45 mA       |
| Cycle time (all channels), min.             | 750 $\mu$ s |

### Output ranges, voltage

- 0 to 10 V Yes; 15 bit
- 1 V to 5 V Yes; 13 bit
- -5 V to +5 V Yes; 15 bit incl. sign
- -10 V to +10 V Yes; 16 bit incl. sign

### Output ranges, current

- 0 to 20 mA Yes; 15 bit
- -20 mA to +20 mA Yes; 16 bit incl. sign
- 4 mA to 20 mA Yes; 14 bit

### Connection of actuators

- for voltage output two-wire connection Yes
- for voltage output four-wire connection Yes
- for current output two-wire connection Yes

### Load impedance (in rated range of output)

- with voltage outputs, min. 2 k $\Omega$
- with voltage outputs, capacitive load, max. 1  $\mu$ F
- with current outputs, max. 500  $\Omega$
- with current outputs, inductive load, max. 1 mH

### Destruction limits against externally applied voltages and currents

|  |   |
|--|---|
| • Voltages at the outputs  | 30 V  |
| <b>Cable length</b>  |   |
| • shielded, max.   | 1 000 m; 200 m for voltage output                       |
| <b>Analog value generation for the outputs</b>                             |   |
| <b>Integration and conversion time/resolution per channel</b>              |   |
| • Resolution with overrange (bit including sign), max.                     | 16 bit  |
| <b>Settling time</b>   |   |
| • for resistive load   | 0.05 ms   |
| • for capacitive load  | 0.05 ms; Max. 47 nF and 20 m cable length               |
| • for inductive load   | 0.05 ms   |
| <b>Errors/accuracies</b>   |   |
| Output ripple (relative to output range, bandwidth 0 to 50 kHz), (+/-)     | 0.02 %  |
| Linearity error (relative to output range), (+/-)                          | 0.03 %  |
| Temperature error (relative to output range), (+/-)                        | 0.003 %/K   |
| Crosstalk between the outputs, max.  | -50 dB  |
| Repeat accuracy in steady state at 25 °C (relative to output range), (+/-) | 0.03 %  |
| <b>Operational error limit in overall temperature range</b>                |   |
| • Voltage, relative to output range, (+/-)                                 | 0.2 %   |
| • Current, relative to output range, (+/-)                                 | 0.2 %   |
| <b>Basic error limit (operational limit at 25 °C)</b>                      |   |
| • Voltage, relative to output range, (+/-)                                 | 0.1 %   |
| • Current, relative to output range, (+/-)                                 | 0.1 %   |
| <b>Isochronous mode</b>  |   |
| Execution and activation time (TCO), min.                                  | 500 µs  |
| Bus cycle time (TDP), min.   | 750 µs  |
| Jitter, max.   | 5 µs  |
| <b>Interrupts/diagnostics/status information</b>                           |   |
| Diagnostics function   | Yes   |
| Substitute values connectable  | Yes   |
| <b>Alarms</b>  |   |
| • Diagnostic alarm   | Yes   |
| <b>Diagnostic messages</b>   |   |
| • Monitoring the supply voltage  | Yes   |
| • Wire-break   | Yes; channel-by-channel, only for output type "current" |
| • Short-circuit  | Yes; channel-by-channel, only for output type "voltage" |
| • Group error  | Yes   |
| • Overflow/underflow   | Yes   |
| <b>Diagnostics indication LED</b>  |   |

- |  |                         |
|--|-------------------------|
| • Monitoring of the supply voltage (PWR-LED) | Yes; green PWR LED      |
| • Channel status display                     | Yes; green LED          |
| • for channel diagnostics                    | Yes; red LED            |
| • for module diagnostics                     | Yes; green/red DIAG LED |

### Potential separation

#### Potential separation channels

- |  |     |
|--|-----|
| • between the channels   | No  |
| • between the channels and backplane bus                       | Yes |
| • between the channels and the power supply of the electronics | Yes |

### Isolation

|                       |                      |
|-----------------------|----------------------|
| Isolation tested with | 707 V DC (type test) |
|-----------------------|----------------------|

### Ambient conditions

#### Ambient temperature during operation

- |                                 |        |
|---------------------------------|--------|
| • horizontal installation, min. | -30 °C |
| • horizontal installation, max. | 60 °C  |
| • vertical installation, min.   | -30 °C |
| • vertical installation, max.   | 50 °C  |

#### Altitude during operation relating to sea level

- |   |  |
|---|--|
| • Installation altitude above sea level, max. | 2 000 m; On request: Installation altitudes greater than 2 000 m |
|---|--|

### Dimensions

|        |       |
|--------|-------|
| Width  | 15 mm |
| Height | 73 mm |
| Depth  | 58 mm |

### Weights

|                 |      |
|-----------------|------|
| Weight, approx. | 31 g |
|-----------------|------|

**last modified:** 05/13/2020