

TR11-C, 1xPt100, 3-w, Cl.B, -50/250°C (F), terminal block, Not removable

TR11-C RTD assembly with fabricated threaded protection tube (tubing)

Item number: 48798805
Quantity: 1 pcs.
Order code: TR11-C-ZZZZ-13DR-BZ2A-ZZ-ATGGDL90050ZZZ00078-ZZZZR12
ZZZZZZZZ-ZA-Z-WIKA0-ZZ
Overview: TR11-C, 1xPt100, 3-w, Cl.B, -50/250°C (F), terminal block, Not removable

Head / housing: BSZ (Alu), Cable gland plastic 6...12 mm, M20 x 1.5
Transmitter: Without (terminal block)

Protection tube: Straight, thread
316L, Ø 6x1 mm, M24 x 1,5 - G1/2B, MH=Without U1=50mm

Sealing: Without
Specifications according to data sheet: TE 60.03

Protection tube total length (spare) [L]: 78 mm

Thermowell specials: Without

Details: TR11-C RTD assembly with fabricated threaded protection tube (tubing)

Specifications according to data sheet: TE 60.03
1xPt100, 3-wire
Class B, IEC 60751
Temperature range of selected class: -50...+250°C
BSZ, Aluminum, ball shaped, flip-top
Cable entry: Cable gland plastic (cable Ø 6...12 mm)
Thread size cable entry: M20 x 1.5
Transmitter: Without (terminal block)
Protection tube: Straight, thread
Connection to neck tube: M24 x 1,5
Protection tube diameter: 6x1 mm
Protection tube material: Stainless steel 316L
Process connection: G 1/2 B
Insertion length [A] [U1]: 50 mm
Neck length [MH/N]: Without
Sealing: Without
Measuring insert: Not removable (no measuring insert)
Thermowell specials: Without