

LOGO! 24CEO, logic module, without display, PS/I/O: 24 V/24 V/24 V trans., 8 DI (4 AI)/4 DQ, memory 400 blocks, modular expandable, Ethernet, integrated web server, data log, user-defined web pages, standard microSD card for LOGO! Soft Comfort V8.3 or higher, older projects executable, cloud connection in all LOGO! 8.3 basic units

### Installation type/mounting

Mounting on 35 mm DIN rail, 4 spacing units wide

### Supply voltage

Rated value (DC)	Yes
<ul style="list-style-type: none"> <li>• 24 V DC</li> </ul>	
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V

### Time of day

Time switching clocks	
<ul style="list-style-type: none"> <li>• Number</li> </ul>	400; Max. 400, function-specific
<ul style="list-style-type: none"> <li>• Power reserve</li> </ul>	480 h

### Digital inputs

Number of digital inputs 8; Of which 4 can be used in analog mode (0 to 10 V)

### Digital outputs

Number of digital outputs	4; Transistor
Short-circuit protection	Yes; electrical (1 A)

### Output current

<ul style="list-style-type: none"> <li>• for signal "1" permissible range for 0 to 55 °C, max.</li> </ul>	0.3 A
---	-------

### EMC

Emission of radio interference acc. to EN 55 011	
<ul style="list-style-type: none"> <li>• Limit class B, for use in residential areas</li> </ul>	Yes; Radio interference suppression according to EN55011, Limit Value Class B

### Standards, approvals, certificates

CE mark	Yes
CSA approval	Yes
UL approval	Yes
FM approval	Yes
developed in accordance with IEC 61131	Yes
according to VDE 0631	Yes
Marine approval	Yes

## Ambient conditions

Ambient temperature during operation	
• min.	-20 °C; No condensation
• max.	55 °C
Ambient temperature during storage/transportation	
• min.	-40 °C
• max.	70 °C
Altitude during operation relating to sea level	
• Ambient air temperature-barometric pressure-altitude	Tmin ... Tmax at 1 080 hPa ... 795 hPa (-1 000 m ... +2 000 m)

## Dimensions

Width	71.5 mm
Height	90 mm
Depth	60 mm
<b>last modified:</b>	10/29/2020