

off switch 100A 2-pole, with red handle



Model	
product brand name	SENTRON
product designation	On/Off switches
design of the product	2 NO red
design of the switching function	Switch disconnecter
General technical data	
number of poles	2
short-circuit current rating	10 kA
Supply voltage	
type of voltage	AC
operating voltage / rated value	440 V
operating frequency	50/60 Hz
Protection class	
protection class IP	Other
Switching capacity	
switching capacity current / rated value	0.3 kA
Dissipation	

power loss [W] / for rated value of the current / at AC / in hot operating state / per pole	5.5 W
---	-------

Main circuit

operating current / rated value	100 A
---------------------------------	-------

Product details

product component / signal lamp	No
number of NO contacts	2

Product function

product function / positive opening (acc. to DIN VDE 0113)	No
connectable conductor cross-section / for flexible conductor / with core end processing	
• minimum	2.5 mm ²
• maximum	50 mm ²
connectable conductor cross-section / for rigid conductor	
• minimum	2.5 mm ²
• maximum	50 mm ²
tightening torque / with screw-type terminals	
• minimum	2.5 N·m
• maximum	3 N·m

Mechanical Design

height	89.8 mm
depth	74.5 mm
installation depth	70 mm
number of width units	2
net weight	221 g
ambient temperature / during operation	
• minimum	-5 °C
• maximum	40 °C
ambient temperature / during storage / minimum	-25 °C

Certificates

General Product Approval



[Miscellaneous](#)



Declaration of Conformity

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)
<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5TL1291-1>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5TL1291-1>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5TL1291-1

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



