

DC 3-/4-wire Inductive Tubular Sensors

Tubular housing, M8x1



M8 x 1	M8 x 1	M8 x 1	M8 x 1	M8 x 1
Flush	Flush	Flush	Flush	Flush
2 mm	2 mm	2 mm	2 mm	2 mm
0...1.6 mm	0...1.4 mm	0...1.6 mm	0...1.4 mm	0...1.6 mm
2X	2X	2X	2X	2X
BES0148	BES0149	BES00P7	BES02P0	BES01AU
BES M08EE-PSC20B-S04G	BES M08EE-PSC20B-S04G-101	BES 516-324-G-E5-C-S49	BES 516-324-SA96-G-E5-C-S49	BES 516-324-G-S49-C
BES0144		BES0113		BES01LP
BES M08EE-POC20B-S04G		BES 516-377-G-E5-C-S49		BES 516-377-G-S49-C
BES0140		BES00TY	BES02P1	
BES M08EE-NSC20B-S04G		BES 516-343-G-E5-C-S49	BES 516-343-SA96-G-E5-C-S49	
BES013U		BES0118		
BES M08EE-NOC20B-S04G		BES 516-378-G-E5-C-S49		
10...30 V DC	10...30 V DC	10...30 V DC	10...30 V DC	10...30 V DC
2.5 V	2.5 V	2.5 V	2.5 V	2.5 V
250 V AC (□)	250 V AC (□)	250 V AC (□)	250 V AC (□)	250 V AC (□)
200 mA	200 mA	200 mA	200 mA	200 mA
Yes/Yes/Yes	Yes/Yes/Yes	Yes/Yes/Yes	Yes/Yes/Yes	Yes/Yes/Yes
-25...+70°C	-25...+70°C	-25...+70°C	-25...+70°C	-25...+70°C
1.5 kHz	1.5 kHz	1.5 kHz	1.5 kHz	1.5 kHz
Yellow LED	Yellow LED	Yellow LED	Yellow LED	Yellow LED
IP 68 per BWN Pr. 20	IP 68 per BWN Pr. 20	IP 68 per BWN Pr. 20	IP 68 per BWN Pr. 20	IP 68 per BWN Pr. 20
CE, cULus	CE, cULus	CE, cULus	CE, cULus	CE, cULus
Stainless steel	Stainless steel	Stainless steel	Stainless steel	Stainless steel
PBT	With ceramic coating	PBT	with ceramic coating	PBT
M12 connector, 4-pin	M12 connector, 4-pin	M8 connector, 3-pin	M8 connector, 3-pin	M8 connector, 3-pin
BCC M415-0000-1A-003-EX44T2-020	BCC M415-0000-1A-003-EX44T2-020	BCC M313-0000-10-001-EX43T2-020	BCC M313-0000-10-001-EX43T2-020	BCC M313-0000-10-001-EX43T2-020



Inductive sensors

Global DC 3-wire

DC 3-/4-wire

Tubular housings

Block housings

DC 2-wire

AC/DC 2-wire

AC 2-wire

Analog distance measurement

Special properties

Special accessories

