



M8 x 1	M8 x 1	M8 x 1	M8 x 1	M8 x 1
Flush	Flush	Flush	Flush	Flush
1.5 mm	1.5 mm	1.5 mm	2 mm	2 mm
0...1.2 mm	0...1.2 mm	0...1.2 mm	0...1.6 mm	0...1.6 mm
1X	1X	1X	2X	2X
BES0027	BES00CU	BES0037	BES00CK	BES00FC
BES M08MH1-PSC15B-S04G	BES M08EF-PSC15B-BP02-003	BES M08MI-PSC15B-BV02	BES M08EE-PSC20B-S49G-003	BES M08EE-PSC20B-S04G-003
BES0026	BES00CR	BES0030	BES00CF	BES00CE
BES M08MH1-POC15B-S04G	BES M08EF-POC15B-BP02-003	BES M08MI-POC15B-BV02	BES M08EE-POC20B-S49G-003	BES M08EE-POC20B-S04G-003
BES0024	BES00CN	BES002F	BES00C9	BES00C8
BES M08MH1-NSC15B-S04G	BES M08EF-NSC15B-BP02-003	BES M08MI-NSC15B-BV02	BES M08EE-NSC20B-S49G-003	BES M08EE-NSC20B-S04G-003
BES0023	BES00CL	BES003PJ	BES00C5	BES00C4
BES M08MH1-NOC15B-S04G	BES M08EF-NOC15B-BP02-003	BES M08MI-NOC15B-BV02	BES M08EE-NOC20B-S49G-003	BES M08EE-NOC20B-S04G-003
12...30 V DC	10...30 V DC	12...30 V DC	10...30 V DC	10...30 V DC
2 V	2.5 V	2 V	2.5 V	2.5 V
75 V DC	250 V AC (□)	75 V DC	250 V AC (□)	250 V AC (□)
200 mA	200 mA	200 mA	200 mA	200 mA
Yes/Yes/Yes	Yes/Yes/Yes	Yes/Yes/Yes	Yes/Yes/Yes	Yes/Yes/Yes
-25...70 °C	-25...70 °C	-25...70 °C	-25...70 °C	-25...70 °C
1 kHz	1 kHz	1 kHz	700 Hz	700 Hz
Yellow LED	Yellow LED	Yellow LED	Yellow LED	Yellow LED
IP 67	IP 67	IP 67	IP 67	IP 67
CE, cULus	CE, cULus	CE, cULus	CE, cULus	CE, cULus
Brass-coated	Stainless steel	Brass-coated	Stainless steel	Stainless steel
PA 12	PBT	PA 12	PBT	PBT
M12 connector, 4-pin	2 m PUR cable, 26 AWG	2 m PVC cable, 26 AWG	M8 connector, 3-pin	M12 connector, 4-pin
BCC M415-0000-1A-003-VX44T2-020-C013			BCC M313-0000-10-001-VX43T2-020-C013	BCC M415-0000-1A-003-VX44T2-020-C013

Inductive sensors

Global DC 3-wire

Tubular housings

Block housings

DC 3-/4-wire

DC 2-wire

AC/DC 2-wire

AC 2-wire

Special properties

Analog distance measurement

Accessories

