


- PNP
- Normally open (NO)
- 2.00 mm
- Flush (shielded)
- Connector, M08x1-S49



General attributes

Approvals / Conformity

CE
cULus
EAC
IEC 60947-5-2
IP68 according to BWN PR 20
Yes
■ ■
Yes
No
II
Yes
830 a

Basic standard

Enclosure Type per IEC 60529

Function indicator

Operating distance marking

Polarity reversal protected

Power indicator

Protection Class

Short circuit protected

MTTF

Electrical attributes

Connection type

Eff. operating current Ie

Eff. operating voltage Ue DC

Electrical version

Load capacitance max. (at Ue)

Max. no-load cur. I_o undamped

Minimum operating current I_m

No-load current I_o damped max.

Operating voltage UB max. DC [V]

Operating voltage UB min. DC [V]

Rated insulation voltage Ui

Rated short circuit current

Ripple max. (% of Ue)

Switching freq. f max. (at Ue)

Connector
200 mA
24.0 V
DC, direct current
0.500 µF
3.0 mA
0 mA
9.0 mA
30.0 V
10.0 V
250 VAC
100 A
15 %
1500 Hz

Switching function

Switching output

Voltage drop static max.

Normally open (NO)

PNP

2.5 V

Mechanical attributes

Ambient temperature Ta max.

Ambient temperature Ta min.

Assured operating distance Sa

Connector type

Depth

Diameter d1

Eff. operating distance Sr

Housing material

Mech. installation condition

Mounting length

Rated operating distance S_n [mm]

Sensing face material

Tightening torque

70 °C

-25 °C

1.60 mm

M08x1-S49

40.0 mm

M08x1

2.00 mm

Stainless steel

Flush (shielded)

29.1 mm

2.00 mm

PBT

8 Nm

Remarks

Embeddable: See installation notes for inductive sensors with extended switching distance 825357.

The sensor is functional again after the overload has been eliminated.

For further information on MTTF/B10d, please refer to the MTTF / B10d Certificate.

Specification of the MTTF value and the B10d value do not represent any binding quality and/or life expectancy guarantees.

