


- PNP
- Normally open (NO)
- 1.50 mm
- Flush (shielded)
- Connector, M12x1-S04



General attributes

| | |
|------------------------------|-----------------------------|
| Approvals / Conformity | CE cULus |
| Basic standard | IEC 60947-5-2 |
| Enclosure Type per IEC 60529 | IP68 according to BWN PR 20 |
| Function indicator | Yes |
| Polarity reversal protected | Yes |
| Power indicator | No |
| Protection Class | II |
| Short circuit protected | Yes |

Electrical attributes

| | |
|--|--------------------|
| Connection type | Connector |
| Eff. operating current I _e | 200 mA |
| Eff. operating voltage U _e DC | 24.0 V |
| Electrical version | DC, direct current |
| Load capacitance max. (at U _e) | 0.500 µF |
| Max. no-load cur. I _o undamped | 3.0 mA |
| Minimum operating current I _m | 0 mA |
| No-load current I _o damped max. | 9.0 mA |
| Operating voltage U _B max. DC [V] | 30.0 V |
| Operating voltage U _B min. DC [V] | 10.0 V |
| Rated insulation voltage U _i | 250 VAC |
| Rated short circuit current | 100 A |

| | |
|---|--------------------|
| Ripple max. (% of U _e) | 15 % |
| Switching freq. f max. (at U _e) | 3000 Hz |
| Switching function | Normally open (NO) |
| Switching output | PNP |
| Voltage drop static max. | 2.5 V |

Mechanical attributes

| | |
|--|------------------|
| Ambient temperature T _a max. | 70 °C |
| Ambient temperature T _a min. | -25 °C |
| Assured operating distance S _a | 1.20 mm |
| Connector type | M12x1-S04 |
| Depth | 58.0 mm |
| Diameter d1 | M08x1 |
| Eff. operating distance S _r | 1.50 mm |
| Housing material | Stainless steel |
| Mech. installation condition | Flush (shielded) |
| Mounting length | 43.0 mm |
| Rated operating distance S _n [mm] | 1.50 mm |
| Sensing face material | PBT |
| Tightening torque | 8 Nm |

Additional text

The sensor is functional again after the overload has been eliminated.

