


- PNP
- Normally open (NO)
- 4.00 mm
- Flush (shielded)
- Cable, PUR, 2.00 m



**General attributes**

Approvals / Conformity	CE cULus
Basic standard	IEC 60947-5-2
Enclosure Type per IEC 60529	IP67
Function indicator	Yes
Operating distance marking	■ ■
Polarity reversal protected	Yes
Power indicator	No
Short circuit protected	Yes
Trademark	GLOBAL

**Electrical attributes**

Connection type	Cable
Eff. operating current I <sub>e</sub>	200 mA
Eff. operating voltage U <sub>e</sub> DC	24.0 V
Electrical version	DC, direct current
Load capacitance max. (at U <sub>e</sub> )	0.500 µF
Max. no-load cur. I <sub>o</sub> undamped	3.0 mA
Minimum operating current I <sub>m</sub>	0 mA
No-load current I <sub>o</sub> damped max.	10.0 mA
Operating voltage U <sub>B</sub> max. DC [V]	30.0 V
Operating voltage U <sub>B</sub> min. DC [V]	10.0 V
Rated insulation voltage U <sub>i</sub>	250 VAC
Rated short circuit current	100 A
Ripple max. (% of U <sub>e</sub> )	15 %
Switching freq. f max. (at U <sub>e</sub> )	300 Hz
Switching function	Normally open (NO)

Switching output	PNP
Voltage drop static max.	2.5 V

**Mechanical attributes**

Ambient temperature T <sub>a</sub> max.	70 °C
Ambient temperature T <sub>a</sub> min.	-25 °C
Assured operating distance S <sub>a</sub>	3.20 mm
Cable diameter D max.	4.6 mm
Cable jacket material	PUR
Cable length	2.00 m
Conductor cross-section	0.34 mm <sup>2</sup>
Depth	33.0 mm
Diameter d1	M12x1
Eff. operating distance S <sub>r</sub>	4.00 mm
Housing material	CuZn
Mech. installation condition	Flush (shielded)
Mounting length	30.0 mm
Number of conductors	3
Rated operating distance S <sub>n</sub> [mm]	4.00 mm
Sensing face material	LCP
Surface protection	Nickel-free coating
Tightening torque	10 Nm

**Additional text**

The sensor is functional again after the overload has been eliminated.  
Embeddable: See installation notes for inductive sensors with extended switching distance 825357.

