


1) Active surface

- PNP
- NO/NC
- 35.00 mm
- Non embeddable
- Connector, M12x1-S04



**General attributes**

Additional features	Factor 1
Approvals / Conformity	cULus
	CE
Basic standard	IEC 60947-5-2
Enclosure Type per IEC 60529	IP67
Function indicator	Yes
Magnetic field immune	immune to magnetic DC and AC fields
Polarity reversal protected	Yes
Power indicator	Yes
Protection Class	II
Short circuit protected	Yes
Trademark	Factor 1

**Electrical attributes**

Connection type	Connector
Eff. operating current I <sub>e</sub>	200 mA
Eff. operating voltage U <sub>e</sub> DC	24.0 V
Electrical version	DC, direct current
Load capacitance max. (at U <sub>e</sub> )	1.000 µF
Magnetic field strength	100 kA/m
Max. no-load cur. I <sub>o</sub> undamped	15.0 mA
Minimum operating current I <sub>m</sub>	0 mA
No-load current I <sub>o</sub> damped max.	20.0 mA
Operating voltage U <sub>B</sub> max. DC [V]	30.0 V
Operating voltage U <sub>B</sub> min. DC [V]	10.0 V
Rated insulation voltage U <sub>i</sub>	250 VAC

Rated short circuit current	100 A
Ripple max. (% of U <sub>e</sub> )	15 %
Switching freq. f max. (at U <sub>e</sub> )	250 Hz
Switching function	NO/NC
Switching output	PNP
Voltage drop static max.	2.5 V

**Mechanical attributes**

Ambient temperature T <sub>a</sub> max.	70 °C
Ambient temperature T <sub>a</sub> min.	-10 °C
Assured operating distance S <sub>a</sub>	28.40 mm
Connector type	M12x1-S04
Depth	62.0 mm
Eff. operating distance S <sub>r</sub>	35.00 mm
Height (small side)	40.0 mm
Housing material	PBT
Mech. installation condition	Non embeddable
Rated operating distance S <sub>n</sub> [mm]	35.00 mm
Sensing face material	PBT
Width (long side)	40.0 mm

**Additional text**

LED 1: Function; LED 2: Operating voltage  
Switching distance specifications and tolerance apply to the shown location of the active surface.  
The sensor is functional again after the overload has been eliminated.

Inductive sensor

**BES Q40KFU-PAC35E-S04G**  
**BES021H**

**BALLUFF**  
*sensors worldwide*

