

Autotransformer E-JET 1000



Advantages

Electronic potential monitoring by not connecting the output voltage until the protected contact plug is inserted correctly

Integrated short circuit and overload protection

Very high efficiency

Very good moisture protection and low noise thanks to XtraDenseFill resin encapsulation

Carrying handle, mains connecting lead and socket NEMA5-15 (USA) for mobile use

Applications

Autotransformer for mobile use for the adjustment of the voltage in 230 Vac networks to 110 Vac equipment when no electrical isolation is required.

Standards

Autotransformer
to: VDE 0570 Teil 2-13, DIN EN 61558-2-13, EN 61558-2-13,
IEC 61558-2-13

Approvals



Autotransformer E-JET 1000

Type		E-JET 1000
Electrical data	Input	
	Rated input voltage	230 Vac
	Rated frequency	50 - 60 Hz
	Output	
	Rated output voltage	110 Vac
	Rated Power	1000 VA
	No-load voltage (app. x factor)	1.03
	Efficiency	96 %
	Environment	
	Ambient temperature max.	40 °C
	Safety and protection	
	Type	Resin encapsulated transformer
	Class of Insulation System	A
	Protection index	IP 22
	Safety class	I
	Short circuit strength	non-inherently short-circuit proof
	Order numbers	
	Order Number	E-JET 1000

Type		E-JET 1000
Mechanical data	Input	
	Terminals Input	Connecting cable with safety plug
	Output	
	Terminals Output	NEMA5-15 socket (USA)
	Measures and weights	
	Weight	9.90 kg
Dimensions W x H x D	143 x 197 x 244 mm	

Subjects to change.