





















COMPLETE CONTROL STATIONS IP66

| Type | Dimensions | Description | Head Colour | Text / Symbol | Contacts | Part Number |
|---|---|--|--------------|-------------------|--------------------|----------------------|
|  |  | Flush pushbutton Spring return | Green | ⓘ | 1 x N/O | LBX10110 |
| | | | Red | ⊙ | 1 x N/C | LBX10610 |
|  |  | Mushroom head Ø40 Spring return | Red | ⊙ | 1 x N/C | LBX10210 |
|  |  | Selector switch 2 position stable | Grey / Black | ⊙ ⓘ | 1 x N/O | LBX12510 |
|  |  | Key switch 2 position stable Supplied With 2 Keys Profile 455 Removable Position 0 1 | Grey / Black | ⊙ ⓘ | 1 x N/O | LBX12610 |
|  |  | Mushroom head Ø40 Turn to reset | Red | EMERGENCY STOP | 1 x N/C | LBX10510 |
|  |  | EN418 Mushroom Head Ø40 Turn To Reset Yellow ring for head position visual indication Conforms to IEC 60947-5-5 / EN418 | Red | EMERGENCY STOP | 1 x N/C 2 x N/C | LBX17301 LBX17302 |
|  |  | EN418 Mushroom Head Ø40 Pull To Reset Yellow ring for head position visual indication Conforms to IEC 60947-5-5 / EN418 | Red | EMERGENCY STOP | 1 x N/C 2 x N/C | LBX15301 LBX15302 |
|  |  | EN418 Mushroom Head Ø40 Key To Reset Yellow ring for head position visual indication Conforms to IEC 60947-5-5 / EN418 Supplied With 2 Keys Profile 455 | Red | EMERGENCY STOP | 1 x N/C 2 x N/C | LBX11301 LBX11302 |
|  |  | EN418 Mushroom Head Ø54 Pull To Reset Flag & ring for head position visual indication Conforms to IEC 60947-5-5 / EN418 | Red | STOP ⓘ STOP ⓘ | 1 x N/C 2 x N/C | LBX13101 LBX13102 |
|  |  | Flush pushbuttons x 2 Spring return | Green & Red | ⓘ ⊙ | 1 x N/O 1 x N/C | LBX20120 |

All enclosures conform to IEC 60947-5-1 and are rated to IP66

All contact blocks are mounted in the rear of the box

Front mounting contacts and other configurations are available please enquire for details