OT125F4C

General Information

 Extended Product Type:
 OT125F4C

 Product ID:
 1SCA105054R1001

 EAN:
 6417019391847

Catalog Description: Manual change-over switch, I-O-II, open transition OT125F4C

Long Description: Manual change-over switch, I-O-II -operation. Include terminal clamps, IP20.

Categories

Products » Low Voltage Products and Systems » Switches » Change-over and Transfer Switches » Manual Change-over Switches

Ordering

 EAN:
 6417019391847

 Minimum Order Quantity:
 1 piece

 Customs Tariff Number:
 85365080

Dimensions

Product Net Width: 193 mm
Product Net Height: 100 mm
Product Net Depth: 86 mm
Product Net Weight: 1.2 kg

Container Information

Package Level 1 Units: 1 piece
Package Level 1 Width: 102 mm
Package Level 1 Height: 103 mm
Package Level 1 Length: 205 mm
Package Level 1 Gross Weight: 1.2 kg
Package Level 1 EAN: 6417019391847

Environmental

RoHS Status: Planned to follow EU Directive 2002/95/EC August 18, 2005 and amendment after 2009 Q3

Additional Information

Cable Cross-Section: 10...70 mm²
Conventional Free-air Thermal q=40°C 125 A

Current (Ith):

Conventional Thermal Current (Ithe): Fully Enclosed 125 A

IIT Publishing Status: Level 0 - Information enabled

Number of Poles: 4

Operating Mechanism: Mechanism on top of the switch

Pollution Degree: 3

Position of Line Terminals:Top in - bottom outPower Loss:Per Pole 6.3 WProduct Main Type:OT125E_125F_CProduct Name:Change-over switch

Rated Impulse Withstand Voltage

(U_{imp}):

8 kV

Rated Insulation Voltage (Ui): 750 V

Rated Operational Current AC-21A (5

(I_e):

A (500V) 125 A (380 ... 415V) 125 A (690V) 125 A

Rated Operational Current AC-22A (I_e):

(-6/-

(380 ... 415 V) 125 A (500 V) 125 A (690 V) 125 A

Rated Operational Current AC-23A

(l_e):

(380 ... 415 V) 90 A (690 V) 50 A (500 V) 70 A

Rated Operational Power AC-23A

(P_e):

(220 ... 240V) 22 kW (400V) 45 kW (415V) 45 kW (500V) 45 kW

(690V) 45 kW

Rated Operational Voltage (U_e): 750 V

Rated Short-time Withstand Current for 1.0s 2.5 kiloampere rms

(I_{cw}):

Certificates and Declarations (Document Number)

Declaration of Conformity - CE: 1SCC303021D0201

Classifications

Object Classification Code:

Q