# S403M-C25

## **General Information**

 Extended Product Type:
 \$403M-C25

 Product ID:
 2CCS573001R0254

 EAN:
 7612270102983

Catalog Description:\$403M-C25 Miniature Circuit Breaker 3 Poles C Characteristic 25A 10000 ~230/400VLong Description:\$403M-C25 Miniature Circuit Breaker 3 Poles C Characteristic 25A 10000 ~230/400V

## Categories

Products » Low Voltage Products and Systems » Modular DIN Rail Products » Plug-in Distribution Systems

Ordering

 EAN:
 7612270102983

 Minimum Order Quantity:
 1 piece

 Customs Tariff Number:
 85363020

#### **Dimensions**

Product Net Width:91 mmProduct Net Height:91 mmProduct Net Length:82 mmProduct Net Weight:0.401 kg

#### **Container Information**

Package Level 1 Units:3 piecePackage Level 1 Width:185 mmPackage Level 1 Height:89 mmPackage Level 1 Length:101 mmPackage Level 1 Gross Weight:1.32 kg

## **Environmental**

RoHS Status: Following EU Directive 2002/95/EC August 18, 2005 and amendment

# **Additional Information**

Frequency (f): 50 ... 60 Hz

IIT Publishing Status: Level 0 - Information enabled

Number of Poles: 3

Power Loss: 6 W

Power Loss: 6 W Product Main Type: S403

Product Name: Plug-in Distribution Systems

10 kA

Rated Current (I<sub>n</sub>): 25 A Rated Operational Current (I<sub>e</sub>): 25 A

Rated Operational Voltage (U<sub>e</sub>): 230 / 400 V AC

Rated Short-Circuit Capacity ( Icn

):

Rated Ultimate Short-Circuit 10 kA

Breaking Capacity (I<sub>cu</sub>):

Rated Voltage ( $U_r$ ): 230 / 400 V

**Standards**: EN60898-1, EN60947-2

Tripping Characteristic: C

# Certificates and Declarations (Document Number)

 Declaration of Conformity - CE:
 2CCY451110D0601

 Environmental Information:
 2CCY000200D0201

 RoHS Information:
 2CCC451021D0201