

# S403M-C32

## General Information

Extended Product Type:	S403M-C32
Product ID:	2CCS573001R0324
EAN:	7612270102990
Catalog Description:	S403M-C32 Miniature Circuit Breaker 3 Poles C Characteristic 32A 10000 ~230/400V
Long Description:	S403M-C32 Miniature Circuit Breaker 3 Poles C Characteristic 32A 10000 ~230/400V

## Categories

Products » Low Voltage Products and Systems » Modular DIN Rail Products » Plug-in Distribution Systems

## Ordering

EAN:	7612270102990
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85363020

## Dimensions

Product Net Width:	91 mm
Product Net Height:	91 mm
Product Net Length:	82 mm
Product Net Weight:	0.401 kg

## Container Information

Package Level 1 Units:	3 piece
Package Level 1 Width:	185 mm
Package Level 1 Height:	89 mm
Package Level 1 Length:	101 mm
Package Level 1 Gross Weight:	1.32 kg

## Environmental

RoHS Status:	Following EU Directive 2002/95/EC August 18, 2005 and amendment
--------------	---

## Additional Information

Frequency (f):	50 ... 60 Hz
IIT Publishing Status:	Level 0 - Information enabled
Number of Poles:	3
Power Loss:	8.1 W
Product Main Type:	S403
Product Name:	Plug-in Distribution Systems
Rated Current ( $I_n$ ):	32 A
Rated Operational Current ( $I_e$ ):	32 A
Rated Operational Voltage ( $U_e$ ):	230 / 400 V AC
Rated Short-Circuit Capacity ( $I_{cn}$ ):	10 kA
Rated Ultimate Short-Circuit Breaking Capacity ( $I_{cu}$ ):	10 kA
Rated Voltage ( $U_r$ ):	230 / 400 V
Standards:	EN60898-1, EN60947-2
Tripping Characteristic:	C

## Certificates and Declarations (Document Number)

Declaration of Conformity - CE:	<a href="#">2CCY451110D0601</a>
Environmental Information:	<a href="#">2CCY000200D0201</a>
RoHS Information:	<a href="#">2CCC451021D0201</a>