## XVSV7BBP

Editable electronic alarms - DIN72 - voice - black - PNP - 12...24V DC



## Main

Range of product	Harmony XVS	
Product or component type	Editable electronic alarm	
Beacon or indicator bank unit typeSound unit		
Device short name	XVSV	

## Complementary

Colour	Dark grey	
Input type	Bit : 6 channel input Binary : 63 channel input	
Assembly style	Ready assembled	
Material	PC (polycarbonate) (body) PC (polycarbonate) (back cover) TPE (thermoplastic elastomer) (front panel) NBR (nitrile butadiene rubber)	
Product weight	0.142 kg	
Marking	CE	
Overvoltage category	Class II conforming to EN/IEC 61140	
Mounting support	72 mm DIN rail	
[Us] rated supply voltage	1224 V DC	
[Ue] rated operational voltage	1030 V DC	
Inrush current	< 30 A	
Associated fuse rating	1 A	
[Uimp] rated impulse withstand voltage	1 kV	
Power consumption	1.8 W	
Current consumption	75 mA at 24 V DC	
Clamping connection capacity	<= 1 x 1.5 mm²	
Device application	Subway Printing Packaging	
Mounting diameter	80 mm	
Width	80 mm	
Height	80 mm	
Depth	24.9 mm	

## **Environment**

Signalling type  Protective treatment  Ambient air temperature for storage  Ambient air temperature for operation  Relative humidity  Adjustable vocal so  TC  -2060 °C  -1055 °C  Relative humidity  3585 % without co	ound
Ambient air temperature for storage -2060 °C  Ambient air temperature for operation -1055 °C	
Ambient air temperature for operation -1055 °C	
Polative humidity 35, 85 % without o	
Relative numbers	condensation
Vibration resistance 7 gn	
IP degree of protection IP65 (panel) confor	rming to EN/IEC 60529

