


MBL1 Multi-function L.E.D. Beacon

The MBL1 is a multi-function L.E.D. beacon featuring a robust, fire retardant, IP66 & IP67 housing; suitable for harsh environments.

The array of 32 high output L.E.D.'s have a total of 9 operating modes; 4 rotating sequences, 4 flashing patterns and a steady mode for indicator or status applications.



Part codes:


Version:	Part code:
24V dc	MBL1DC24G-[xx]
48V dc	MBL1DC24G-[xx]
24V ac	MBL1AC24G-[xx]
115V ac	MBL1AC115G-[xx]
230V ac	MBL1AC230G-[xx]
[xx] = L.E.D. / Lens colour:	AM: Amber, BL: Blue, GN: Green, RD: Red, YW: Yellow

Current consumption:

Version:	Voltage:	Current:
24V dc	10-50V dc	400mA
48V dc	10-50V dc	230mA
24V ac	50/60Hz +/-10%	380mA
115V ac	50/60Hz +/-10%	140mA
230V ac	50/60Hz +/-10%	70mA

Flash patterns:

Stage 1: [Selectable on board]	Stage 2: [Remotely selectable]	Stage 3: [Remotely selectable]
All L.E.D.'s on	Alt Side Flash 1:1 2Hz	2x Flash 2Hz
Rotating: Fast 1	Rotating: Fast 2	All L.E.D.'s on
Rotating: Fast 2	Double Strike Flash 2Hz	All L.E.D.'s on
Rotating: Slow 1	Alt Side Flash 1:1 2Hz	All L.E.D.'s on
Rotating: Slow 2	2x Flash 1Hz	All L.E.D.'s on
2x Flash 1Hz	Alt Side Flash 1:1 2Hz	All L.E.D.'s on
1x Flash 2Hz	Rotating: Fast 2	All L.E.D.'s on
2x Flash 2Hz	Rotating: Fast 2	All L.E.D.'s on
Alt Side Flash 1:1 2Hz	Rotating: Fast 2	All L.E.D.'s on



Specification:

Light source:	Array of 32 high output L.E.D.s
Peak candela:	11 cd* - measured ref. to I.E.S.
Effective candela:	11 cd* - measured ref. to I.E.S.
Lens colours:	Amber, Blue, Green, Red & Yellow
Voltages DC:	10-50V dc
Voltages AC:	24V ac; 115V ac; 230V ac
Ingress protection:	IP66 & IP67 (Third party tested)
Housing material:	High impact UL94 V0 & 5VA FR ABS
Colour:	Grey (RAL7038)
Cable entries:	2 x M20 supplied with 1 blanking plug
Lens material:	Borosilicate glass dome with PC prismatic lens cover.
Guard:	Stainless Steel dome guard as standard
Terminals:	0.5 to 4.0mm ² cables.
Operating temp:	-25 to +55°C
Storage temp:	-40 to +70°C
Relative humidity:	90% at 20°C.
Weight:	1.48kg

*Candela measurements representative of performance with clear lens at optimum voltage.

Features:

- Continuously rated.
- Large termination area.
- Stainless steel fixings.
- Ratchet adjustable stainless steel 'U' bracket for 360° positioning.
- Duplicate cable terminations (in & out for daisy-chain installations).
- Tropicalisation available on request.

Approvals:

- GOST-R approved. Cert: POCC GB.JB05.H00144.