SIEMENS

Data sheet 6GK5908-0PB00

Product type designation

Product description

KEY-PLUG SINEMA RC

Removable medium for activating SINEMA RC for SCALANCE M-800 / S615 and for simple device replacement in the event of a fault KEY-PLUG SINEMA RC, Removable data storage medium for enabling of the connection to SINEMA Remote Connect for S615 and SCALANCE M for simple device replacement in event of fault and for Recording of configuration data



Suitability for use	Activation of SINEMA RC
Ambient conditions	
Ambient temperature	
during operation	-40 +75 °C
during storage	-40 +80 °C
 during transport 	-40 +80 °C
Relative humidity	
 at 25 °C / without condensation / during operation / maximum 	95 %
Protection class IP	IP20
Design, dimensions and weights	
Width	24.3 mm
Height	17 mm
Depth	8.1 mm
Net weight	5 g
design of the removable storage	

• C-PLUG No

• KEY-PLUG Yes

Product features, product functions, product components / general

Standards, specifications, approvals

Reference code

Storage capacity

according to IEC 81346-2:2018

CFA

256 Mibyte

Further information / Internet-Links

Internet-Link

• to website: TIA Selection Tool

• to website: Selector SIMATIC NET

SELECTION TOOL

• to the website: IWLAN

• to website: Industrial communication

• to website: Industry Mall

• to website: Information and Download Center

• to website: Image database

• to website: CAx Download Manager

• to website: Industry Online Support

http://www.siemens.com/tia-selection-tool

http://www.siemens.com/snst

http://www.siemens.com/iwlan

http://www.siemens.com/simatic-net

https://mall.industry.siemens.com

http://www.siemens.com/industry/infocenter

http://automation.siemens.com/bilddb

http://www.siemens.com/cax

https://support.industry.siemens.com

last modified: 05/08/2020