



solenoid valve

VUVG-B10-P53C-ZT-F-1T1L

Part number: 573419

FESTO



Data sheet

| Feature | Value |
|---|--|
| Valve function | 5/3 closed |
| Type of actuation | electrical |
| Valve size | 10 mm |
| Standard nominal flow rate | 200 l/min |
| Operating pressure | -0.9 ... 10 bar |
| Design structure | Piston slide |
| Protection class | IP65 IP67 |
| Authorisation | c CSA us (OL) c UL us - Recognized (OL) |
| Exhaust-air function | throttleable |
| Sealing principle | soft |
| Assembly position | Any |
| Manual override | detenting Pushing |
| Type of piloting | Piloted |
| Pilot air supply | external |
| Flow direction | reversible |
| Signal status display | LED |
| Pilot pressure | 3 ... 8 bar |
| Max. switching frequency | 3 Hz |
| Switching time off | 38 ms |
| Switching time on | 12 ms |
| Switching time reversal | 16 ms |
| Duty cycle | 100% |
| Max. positive test pulse with logic 0 | 1,600 µs |
| Max. negative test pulse with logic 1 | 3,000 µs |
| Characteristic coil data | 22 V DC: 1 W |
| Permissible voltage fluctuation | +/- 10 % |
| Operating medium | Compressed air in accordance with ISO8573-1:2010 [7:4:4] |
| Note on operating and pilot medium | Lubricated operation possible (subsequently required for further operation) |
| Vibration resistance | Transport application test at severity level 2 in accordance with FN 942017-4 and EN 60068-2-6 |
| Shock resistance | Shock test with severity level 2 in accordance with FN 942017-5 and EN 60068-2-27 |
| Corrosion resistance classification CRC | 2 - Moderate corrosion stress |
| Medium temperature | -5 ... 60 °C |
| Pilot medium | Compressed air in accordance with ISO8573-1:2010 [7:4:4] |
| Ambient temperature | -5 ... 60 °C |
| Product weight | 58 g |
| Electrical connection | via manifold block |
| Mounting type | on manifold rail |
| Materials note | Conforms to RoHS |
| Material seals | HNBR NBR |
| Material housing | Wrought Aluminium alloy |